

Introduction

MELTRIC Overview	pg 2
Product Features & Benefits	pg 4
Product Summary & Selection Guide	pg 8
Part Number & Ordering Guide	pg 14
Switch-Rated Plugs & Receptacles	
The Main Differences	pg 16
Selection Guide	pg 20
DSN Type 4X/IP69k rated, metal or poly casings. From 20 – 150A (1/2 – 75 hp)	pg 22
DS Type 3R rated, metal or poly casings. From 20 – 200A (3/4 – 50 hp)	pg 38
DB IP67 rated, metal casings. From 30 – 100A (2 – 60 hp)	pg 56

Multipin Plugs & Receptacles

Multipin 4 – 37 pin connectors in poly and metal. From 2 – 150A	pg 70
--	-------

Standard Duty Plugs & Receptacles

DR Type 3R rated, poly or metal casings. From 30 – 400A	pg 96
PN IP66/IP67 rated or IP54 rated, poly or metal. 20A	pg 114
High Temp For environments up to 465°F (240°C)	pg 122

Direct Current Plugs & Receptacles

DSDC DC current rated, poly or metal casings. Up to 750 VDC	pg 126
--	--------

High Ampacity Plugs & Receptacles

PF/PFQ IP66/IP67 rated, metal construction. From 300 – 600A	pg 132
DR400 Type 3R rated, metal casings. 400A	pg 140
SP Single pole, connectors up to 600A	pg 144
CS1000 Single pole, connectors up to 400A	pg 148

Power Distribution

Custom Power Distribution Solutions Built specifically to meet customer needs	pg 154
Integral Circuit Protection Wall Boxes Premounted receptacles wired to circuit protection 20-60A	pg 162
GFCI Combinations Premounted receptacles wired to GFCI boxes 20-60A	pg 168
Safety Switch/Receptacle Combinations Switch-rated receptacles mounted to single throw, fusible safety switch	pg 170

Specialty Products

WS – Welding Connectors Single pole connectors (max 50 VAC)	pg 174
Adapter Plates For converting existing receptacles to MELTRIC	pg 175
Cord Grips	pg 178
Voltage/Phase Rotation Meter Assemblies	pg 180

Hazardous Location Plugs & Receptacles

Hazardous Duty Selection Guide	pg 184
DXN Hazardous rated, poly casings. From 20 – 60A (1/4 – 20 hp)	pg 186
DXA Hazardous rated, metallic casings. From 20 – 100A	pg 198
DS60/DSN150 Hazardous rated, metallic casings. 60 & 150A (up to 75 hp)	pg 202
DX Hazardous rated, metallic casings. From 20 – 125A	pg 208
Multipin Hazardous rated, 12 to 37 pins, 10A	pg 218
SPeX Hazardous rated, up to 680A, 1000VAC	pg 224