





# MELTRIC PRODUCT SUMMARY...

	Model	Amp Rating	Maximum Voltage Rating		Environmental Ratings		Available Casing Materials			Maximum Number of Contacts	
			VAC	VDC	Type	IP	Poly	Metal	SS	Main	Aux.
<b>Switch-Rated</b>	 DSN20	20	600	-	4X	69k	Poly	-	-	3P+N+G	2
	DSN30	30	600	-	4X	69k	Poly	-	-	3P+N+G	2
	DSN60	60	600	-	4X	69k	Poly	-	-	3P+N+G	4
	DSN150	150	600	-	4X	69k	Poly	Metal	-	3P+N+G	6
	DS20	20	600	-	3R	-	Poly	-	-	3P+N+G	2
	DS30	30	600	-	3R	-	Poly	-	-	3P+N+G	4
	 DS60	60	600	-	3R	-	Poly	Metal	-	3P+N+G	4
	DS100C	100	600	-	3R	-	Poly	Metal	-	3P+N+G	4
	DS100	100	600	-	3R	-	Poly	Metal	-	3P+N+G	6
	DS200	200	480	-	3R	-	-	Metal	-	3P+N+G	4
	 DB30	30	600	-	-	67	-	Metal	-	3P+N+G	2
	DB60	60	600	-	-	67	-	Metal	-	3P+N+G	2
	DB100	100	600	-	-	67	-	Metal	-	3P+N+G	4
	<b>Multipin</b>	 PN7c	15	600	130	-	66/67*	Poly	Metal	SS	6P+G
PN7c		20	600	130	-	66/67*	Poly	Metal	SS	6P+G	-
PN12c		5	600	-	-	66/67*	Poly	Metal	SS	11P+G	-
PN12c		7.5	600	-	-	66/67*	Poly	Metal	SS	11P+G	-
DSN24c		2	480	130	-	66/67	Poly	-	-	24	-
DSN24c		7.5	480	130	-	66/67	Poly	-	-	24	-
DS24c		2	250	130	-	-	-	-	SS	24	-
DS24c		7.5	250	130	-	-	-	-	SS	24	-
DSN37c		2	480	130	-	66/67	Poly	-	-	37	-
DSN37c		7.5	480	130	-	66/67	Poly	-	-	37	-
DS37c		2	480	130	-	-	-	-	SS	37	-
DS37c		7.5	480	130	-	-	-	-	SS	37	-




\* The indicated ratings do not apply to devices with SS casings.

# ...AND SELECTION GUIDE

Model	Current Interruption Rating*	Horsepower Ratings (see catalog section for other voltages)			Main Contacts Wire Size Capacity		Terminal Type
		240V - 3Ø	480V - 3Ø	600V - 3Ø	Min	Max	
<b>DSN20</b>	Switch-Rated	2 hp	5 hp	5 hp	14 AWG	12 AWG	Screw
<b>DSN30</b>	Switch-Rated	5 hp	10 hp	15 hp	14 AWG	8 AWG	Screw
<b>DSN60</b>	Switch-Rated	7 ½ hp	20 hp	20 hp	12 AWG	4 AWG	Screw
<b>DSN150</b>	Switch-Rated	30 hp	75 hp	75 hp	4 AWG	2/0 AWG	Screw
<b>DS20</b>	Switch-Rated	5 hp	7.5 hp	10 hp	14 AWG	8 AWG	Screw
<b>DS30</b>	Switch-Rated	5 hp	15 hp	15 hp	14 AWG	4 AWG	Screw
<b>DS60</b>	Switch-Rated	10 hp	25 hp	25 hp	10 AWG	2 AWG	Screw
<b>DS100C</b>	Switch-Rated	20 hp	50 hp	50 hp	10 AWG	2 AWG	Screw
<b>DS100</b>	Switch-Rated	10 hp	30 hp	-	4 AWG	2/0 AWG	Screw
<b>DS200</b>	Switch-Rated	-	-	-	4 AWG	4/0 AWG	Screw
<b>DB30</b>	Switch-Rated	7 ½ hp	20 hp	25 hp	14 AWG	8 AWG	Screw
<b>DB60</b>	Switch-Rated	15 hp	30 hp	30 hp	8 AWG	3 AWG	Screw
<b>DB100</b>	Switch-Rated	30 hp	60 hp	60 hp	1/0 AWG	2/0 AWG	Screw
<b>PN7c</b>	Current Interrupting	-	-	-	18 AWG	10 AWG	Screw
<b>PN7c</b>	Non-Current Interrupting	-	-	-	18 AWG	10 AWG	Screw
<b>PN12c</b>	Current Interrupting	-	-	-	18 AWG	14 AWG	Solder/Crimp
<b>PN12c</b>	Non-Current Interrupting	-	-	-	18 AWG	14 AWG	Solder/Crimp
<b>DSN24c</b>	Current Interrupting	-	-	-	18 AWG	14 AWG	Solder/Crimp
<b>DSN24c</b>	Non-Current Interrupting	-	-	-	18 AWG	14 AWG	Solder/Crimp
<b>DS24c</b>	Current Interrupting	-	-	-	18 AWG	14 AWG	Solder/Crimp
<b>DS24c</b>	Non-Current Interrupting	-	-	-	18 AWG	14 AWG	Solder/Crimp
<b>DSN37c</b>	Current Interrupting	-	-	-	18 AWG	14 AWG	Solder/Crimp
<b>DSN37c</b>	Non-Current Interrupting	-	-	-	18 AWG	14 AWG	Solder/Crimp
<b>DS37c</b>	Current Interrupting	-	-	-	18 AWG	14 AWG	Solder/Crimp
<b>DS37c</b>	Non-Current Interrupting	-	-	-	18 AWG	14 AWG	Solder/Crimp

\* 'Switch-Rated' and 'Current Interrupting' ratings apply to alternating current only.

# MELTRIC PRODUCT SUMMARY...

	Model	Amp Rating	Maximum Voltage Rating		Environmental Ratings		Available Casing Materials			Maximum Number of Contacts	
			VAC	VDC	Type	IP	Poly	Metal	SS	Main	Aux.
<b>Multipin</b> 	DN9c	20	480	130	-	54/55	-	Metal	-	9	-
	DN20c	20	480	130	-	54/55	-	Metal	-	20	-
	DS7c	30	600	130	-	54/55	Poly	Metal	-	7	3
	DR7c	50	600	130	-	54/55	Poly	Metal	-	7	3
<b>Standard</b> 	DR30	30	600	-	3R	-	Poly	-	-	3P+N+G	2
	DR50	50	600	-	3R	-	Poly	-	-	3P+N+G	4
	DR100	100	600	-	3R	-	Poly	Metal	-	3P+N+G	4
	DR150	150	600	-	3R	-	Poly	Metal	-	3P+N+G	6
	DR250	250	600	-	3R	-	-	Metal	-	3P+N+G	4
	DR400	400	480**	-	3R	-	-	Metal	-	3P+N+G	2
	PN	15	600	-	-	55 or 66+67*	Poly	Metal	SS	3P+N+G	-
	PN	20	480	-	-	55 or 66+67*	Poly	Metal	SS	3P+N+G	-
	PNHT	30	480	-	-	44	-	Metal	-	3P+N+G	-
	<b>Direct Current</b> 	DSDC1	20	-	250	3R	-	Poly	-	-	2P+G
DSDC1		15	-	600	3R	-	Poly	-	-	2P+G	0
DSDC1		10	-	750	3R	-	Poly	-	-	2P+G	0
DSDC3		30	-	250	3R	-	Poly	-	-	2P+G	0
DSDC3		30	-	600	3R	-	Poly	-	-	2P+G	0
DSDC3		20	-	750	3R	-	Poly	-	-	2P+G	0
DSDC6		60	-	250	3R	-	Poly	Metal	-	2P+G	0
DSDC6		50	-	600	3R	-	Poly	Metal	-	2P+G	0
DSDC6		30	-	750	3R	-	Poly	Metal	-	2P+G	0
DSDC9		100	-	250	3R	-	Poly	Metal	-	2P+G	0
DSDC9		60	-	600	3R	-	Poly	Metal	-	2P+G	0
DSDC2		200	-	250	3R	-	-	Metal	-	2P+G	0
DSDC2		100	-	600	3R	-	-	Metal	-	2P+G	0

\* The indicated ratings do not apply to devices with SS casings.

\*\* 600V available at 350 amps.





















<sup>1</sup> Up to 250VAC.

# ...AND SELECTION GUIDE

Model	Current Interruption Rating*	Horsepower Ratings (see catalog section for other voltages)			Main Contacts Wire Size Capacity		Terminal Type
		240V - 3Ø	480V - 3Ø	600V - 3Ø	Min	Max	
<b>DN9c</b>	Current Interrupting	3 hp	5 hp	-	16 AWG	10 AWG	Screw
<b>DN20c</b>	Current Interrupting	1 hp	3 hp	-	16 AWG	10 AWG	Screw
<b>DS7c</b>	Current Interrupting	-	-	-	14 AWG	8 AWG	Screw
<b>DR7c</b>	Non-Current Interrupting	-	-	-	14 AWG	8 AWG	Screw
<b>DR30</b>	Non-Current Interrupting	-	-	-	14 AWG	8 AWG	Screw
<b>DR50</b>	Current Interrupting	-	-	-	14 AWG	4 AWG	Screw
<b>DR100</b>	Current Interrupting	-	-	-	10 AWG	2 AWG	Screw
<b>DR150</b>	Current Interrupting	-	-	-	4 AWG	2/0 AWG	Screw
<b>DR250</b>	Non-Current Interrupting	-	-	-	4 AWG	4/0 AWG	Screw
<b>DR400</b>	Non-Current Interrupting	-	-	-	2 AWG	500 MCM	Screw
<b>PN</b>	Current Interrupting	-	-	-	14 AWG	8 AWG	Screw
<b>PN</b>	Current Interrupting	-	-	-	14 AWG	8 AWG	Screw
<b>PNHT</b>	Non-Current Interrupting	-	-	-	14 AWG	8 AWG	Screw
<b>DSDC1</b>	Non-Current Interrupting	-	-	-	14 AWG	8 AWG	Screw
<b>DSDC1</b>	Non-Current Interrupting	-	-	-	14 AWG	8 AWG	Screw
<b>DSDC1</b>	Non-Current Interrupting	-	-	-	14 AWG	8 AWG	Screw
<b>DSDC3</b>	Non-Current Interrupting	-	-	-	14 AWG	6 AWG	Screw
<b>DSDC3</b>	Non-Current Interrupting	-	-	-	14 AWG	6 AWG	Screw
<b>DSDC3</b>	Non-Current Interrupting	-	-	-	14 AWG	6 AWG	Screw
<b>DSDC6</b>	Non-Current Interrupting	-	-	-	10 AWG	2 AWG	Screw
<b>DSDC6</b>	Non-Current Interrupting	-	-	-	10 AWG	2 AWG	Screw
<b>DSDC6</b>	Non-Current Interrupting	-	-	-	10 AWG	2 AWG	Screw
<b>DSDC9</b>	Non-Current Interrupting	-	-	-	8 AWG	2/0 AWG	Screw
<b>DSDC9</b>	Non-Current Interrupting	-	-	-	8 AWG	2/0 AWG	Screw
<b>DSDC2</b>	Non-Current Interrupting	-	-	-	4 AWG	2/0 AWG	Screw
<b>DSDC2</b>	Non-Current Interrupting	-	-	-	4 AWG	2/0 AWG	Screw

\* 'Current Interrupting' rating applies to alternating current only.

# MELTRIC PRODUCT SUMMARY...

	Model	Amp Rating	Maximum Voltage Rating		Environmental Ratings		Available Casing Materials			Maximum Number of Contacts	
			VAC	VDC	Type	IP	Poly	Metal	SS	Main	Aux.
<b>High Ampacity</b>	 PFQ	300	600	250	-	66/67	-	Metal	-	3P+N+G	8
	 PF300	300	600	250	-	66/67	-	Metal	-	3P+N+G	4
	 PF400	400	600	250	-	66/67	-	Metal	-	3P+N+G	4
	 PF600	600	600	250	-	66/67	-	Metal	-	3P+N+G	4
	 SP	600	600	1500	-	66/67	Poly	-	-	1P	-
	 CS1000	400	1000	1500	-	66/67	Poly	-	-	1P	-
<b>Hazardous Location</b>	 DXN20	20	480	-	-	66/67	Poly	-	-	3P+N+G	-
	 DXN30	30	600	-	-	66/67	Poly	-	-	3P+N+G	2
	 DXN60	60	600	-	-	66/67	Poly	-	-	3P+N+G	2
	 DXA1	20	550	-	-	66/67	-	Metal	-	3P+N+G	-
	 DS60	60	600	-	4X	-	-	Metal	-	3P+N+G	2
	 DSN150	150	600	-	4X	-	-	Metal	-	3P+N+G	6
	 DX1	20	600	-	-	65	-	Metal	-	3P+N+G	-
	 DX3	32	600	-	-	65	-	Metal	-	3P+N+G	-
	 DX6	63	600	-	-	65	-	Metal	-	3P+N+G	-
	 DX9	125	600	-	-	65	-	Metal	-	3P+N+G	-
	 PXN12c	10	220	-	-	65/66	-	Metal	-	12	-
	 DXN25c	10	440	-	-	66/67	-	Metal	-	25	-
	 DXN37c	10	220	-	-	66/67	-	Metal	-	37	-
	 SPeX	680	1000	-	-	65/66	Poly	-	-	1P	-

# ...AND SELECTION GUIDE

Model	Current Interruption Rating	Horsepower Ratings (see catalog section for other voltages)			Main Contacts Wire Size Capacity		Terminal Type
		240V - 3Ø	480V - 3Ø	600V - 3Ø	Min	Max	
<b>PFQ</b>	Non-Current Interrupting	-	-	-	2 AWG	600 MCM	Lug
<b>PF300</b>	Non-Current Interrupting	-	-	-	2 AWG	600 MCM	Lug
<b>PF400</b>	Non-Current Interrupting	-	-	-	2 AWG	600 MCM	Lug
<b>PF600</b>	Non-Current Interrupting	-	-	-	2 AWG	600 MCM	Lug
<b>SP</b>	Non-Current Interrupting	-	500 hp	500 hp	2/0 AWG	777 MCM	Lug
<b>CS1000</b>	Non-Current Interrupting	-	-	-	2/0 AWG	444 MCM	Lug
<b>DXN20</b>	Current Interrupting	2 hp	5 hp	5 hp	16 AWG	10 AWG	Screw
<b>DXN30</b>	Current Interrupting	5 hp	10 hp	15 hp	14 AWG	6 AWG	Screw
<b>DXN60</b>	Current Interrupting	5 hp	20 hp	20 hp	10 AWG	4 AWG	Screw
<b>DXA1</b>	Current Interrupting	-	-	-	16 AWG	10 AWG	Screw
<b>DS60</b>	Non-Current Interrupting	10 hp	20 hp	25 hp	10 AWG	2 AWG	Screw
<b>DSN150</b>	Non-Current Interrupting	30 hp	75 hp	75 hp	4 AWG	2/0 AWG	Screw
<b>DX1</b>	Current Interrupting	-	-	-	14 AWG	8 AWG	Screw
<b>DX3</b>	Current Interrupting	-	-	-	14 AWG	8 AWG	Screw
<b>DX6</b>	Current Interrupting	-	-	-	6 AWG	1/0 AWG	Screw
<b>DX9</b>	Current Interrupting	-	-	-	1/0 AWG	2/0 AWG	Screw
<b>PXN12c</b>	Non-Current Interrupting	-	-	-	16 AWG	14 AWG	Solder/Crimp
<b>DXN25c</b>	Non-Current Interrupting	-	-	-	16 AWG	14 AWG	Solder/Crimp
<b>DXN37c</b>	Non-Current Interrupting	-	-	-	16 AWG	14 AWG	Solder/Crimp
<b>SPeX</b>	Non-Current Interrupting	-	-	-	2/0 AWG	750 MCM	Lug