

## New Cable Reducing Adapters and New Metal Angle (DR400)

### new product description

For DR400 applications with wire size exceeding 350 MCM, MELTRIC now offers:





#### Cable Reducing Adapters and New Extended Metal 60° Angle with a 68 mm Spacer



Cable Reducing Adapters - enable up to 500 MCM to fit into our 350 MCM terminals.



New spacious angle accessory provides space for cable reducing adapters.

	Part Number	Description	Comment
	5T7M6-68	Extended Metal 60° Angle with 68 mm spacer	Includes the new angle and a 68 mm spacer (both are required when using cable reducers)
 Flared opening	PT535FX350-3	Reducer for 500 MCM Fine Stranded or Flexible Wire	Typically used on Inlet/Cord Side
 Straight opening	PT500R350-3	Reducer for 500 MCM Coarse Stranded or Building Wire	Typically used on Receptacle/Wall Side
 Straight opening	PT400R350-3	Reducer for 400 MCM Wire	Use on Inlet or Receptacle

### order examples

#### Mounting on angle

Typical DR400 receptacle using 500 MCM building wire on the three phase contacts would require:



(3pc) PT500R350-3  
Reducers

+



(1pc) 5T7M6-68  
Extended Metal 60°  
Angle + 68 mm spacer

#### Mounting on handle

Reducers may be used with 4MHXXX Metal Handle with no special provisions required.



(3pc) PT535FX350-3  
Reducers

+



(1pc) 4MHXXX  
Metal Handle  
\*2018 part # 5T7P0NXX