

HP Rating Improvements: DXN model

product improvement description

Recent successful performance tests results have allowed Meltric to upgrade horsepower ratings on all DXN models. Effective immediately, DXN inlets and receptacles will be horsepower rated according to the table below.

NEW

DXN Horsepower Ratings

| Model | DXN | | |
|---------|--------|--------|--------|
| | 20 | 30 | 60 |
| 120V 1Ø | 1/2 hp | 1 hp | 2 hp |
| 208V 1Ø | 1 hp | 2 hp | 3 hp |
| 240V 1Ø | 1.5 hp | 3 hp | 3 hp |
| 277V 1Ø | 2 hp | 3 hp | 5 hp |
| 480V 1Ø | 3 hp | 5 hp | 7.5 hp |
| 600V 1Ø | 3 hp | 7.5 hp | 10 hp |
| 208V 3Ø | 2 hp | 5 hp | 7.5 hp |
| 240V 3Ø | 2 hp | 5 hp | 7.5 hp |
| 480V 3Ø | 5 hp | 10 hp | 20 hp |
| 600V 3Ø | 5 hp | 15 hp | 20 hp |



communication plan

- The Meltric website is in the process of being updated to reflect the new ratings.
- All digital literature on the site will be updated in the next few days.
- Paper copies of the catalog will be updated when existing inventory is depleted. (Please note that the next catalog will likely be printed in May 2016.)
- A new version of the DXN-HP flyer is available to order. Please recycle the old version, rev A.