

Enclosed Arc Chambers

Eliminate exposure to arcing during disconnection.

Dead-Front Safety Shutter

Assures safety by preventing user access to live parts after the plug is removed.

Silver-Nickel Contact Tips

Silver-nickel material offers exceptional electrical properties and resistance to wear, welding, corrosion, and oxidation.

Watertight Seal

Rated watertightness up to Type 4X/IP69/IP69K is achieved as soon as the plug mates with the receptacle.

Push-Button Disconnection

Provides quick, safe, and easy load break.

Spring-Assisted Screw Terminals

Patented design assures "Tighten and Forget" confidence.

Durable Casing Materials

Rugged, impact-resistant casings withstand harsh environmental conditions.

Spring-Loaded, Butt-Style Contacts
Ensure optimal contact force and high
conductivity over thousands of operations.



Tested to a Higher Standard

Unlike standard pin and sleeve devices, which are evaluated to UL 1682/CSA c22.2 No. 182.1, MELTRIC Switch-Rated plugs and receptacles are additionally performance tested and listed to UL Subject 2682 "Switch-Rated Plugs and Receptacles." This provides the basis for their UL/CSA certification for use in motor circuit and branch circuit disconnect switching applications.

Key performance tests required for MELTRIC's Switch-Rated listings per UL Subject 2682:

- 50 operations @ 600% Full Load motor current with .4-.5 power factor
- 6,000 operations @ Rated Current and Voltage with .75-.8 power factor
- Short circuit make and withstand @ ≥10kA*, 600V and ≤ .50 PF

^{*}Device ratings range from 10kA to 100kA.



Spring-Loaded, Silver-Nickel Butt-Style Contacts make the difference between ordinary and Switch-Rated plugs and receptacles.





meltric.com

4765 W. Oakwood Park Drive • Franklin, WI 53132 800-433-7642

©2024 MELTRIC Corporation. All rights reserved. DECMAILER G



SWITCH-RATEDPLUGS AND RECEPTACLES

Featuring DECONTACTOR™ Technology





DECONTACTOR™ **Technology** Advantages



Ensure User Safety

MELTRIC® Switch-Rated plugs and receptacles are designed for safety. They safely make and break connections under full load and eliminate the hazards associated with pin and sleeve devices.

- No pulling an arc during disconnection
 - No exposure to live parts
- No brass contacts to degrade. weld, or fail during use
- No failure from terminal screw loosening

MELTRIC Switch-Rated plugs and receptacles are also rated to make into and withstand short circuit currents up to 100 kA when protected with RK1 fuses.





Watertightness ratings up to Type 4X/IP69/IP69K are achieved automatically, so there is no need to thread on special watertightness rings.





MELTRIC Switch-Rated plugs and receptacles can be easily locked out and tagged out, only your lock and tag are needed.



Simplify Code Compliance and Reduce Costs

MELTRIC® Switch-Rated plugs and receptacles are UL/CSA rated for branch circuit and motor circuit disconnect switching up to 200 A and 100 hp. Using them to connect electrical equipment automatically provides the NEC-required line-of-sight disconnect, which:



Simplifies code compliance.

Eliminates the need for separate disconnect switches or mechanical interlocks.





When you purchase a MELTRIC Switch-Rated plug and receptacle, you effectively get the disconnect switch for free.



Reduce Equipment Changeout Time

Using MELTRIC® Switch-Rated plugs and receptacles to connect motors and other critical equipment allows changeouts to be performed without the need for wiring work.

- No waiting for an electrician
- No suiting up in cumbersome PPE
- No rewiring for proper rotation

Critical processes are back up and running in a fraction of the time.

The electrical work to pre-wire replacement motors and ensure proper phase rotation is done at a convenient time back at the shop.

A dead-front safety shutter helps users avoid the need for cumbersome PPE, and allows faster and safer equipment changeouts.



