

DS20 Switch-Rated Plugs & Receptacles – 20 A

UL/CSA Ratings

- **Max Amperage & Voltage**
20 A, 600 VAC
- **Switch-Rating (AC Only)**
Branch Circuit & Motor Circuit
Disconnect Switching
- **Horsepower Ratings**

120 V	1Ø	.75 hp
208 V	3Ø	3 hp
240 V	3Ø	5 hp
480 V	3Ø	7.5 hp
600 V	3Ø	10 hp
- **Short Circuit Rating**
100 kA Close & Withstand
Tested with RK1 current limiting
fuses sized at 400% of the highest
full load motor ampacity.
- **Environmental Ratings**
Type 3R (Standard)
Type 4X (Optional)
- **Temperature Range**
Min -40°F/Max 140°F
See pg 266 for temps below -15°F.
- **Wiring Capacity**
Min 14 AWG Max 8 AWG
Aux Contact - Max 14 AWG
Based on THHN wire sizes.
- **Certifications**
UL 2682, UL 1682, CSA 182.1

Receptacle (female)



Inlet (male)



! Don't forget to add installation accessories to your order

North American UL/CSA Configurations

Voltage	Polarity	Part # Poly	Part # Poly
120 V	1P+N+G	33-14165	33-18165
120 208 V	3P+N+G	33-14167	33-18167
125 V	1P+N+G	33-14075	33-18075
125 250 V	2P+N+G	33-14076	33-18076
208 V	2P+G	33-14162	33-18162
208 V	3P+G	33-14163	33-18163
250 V	2P+G	33-14072	33-18072
250 V	3P+G	33-14073	33-18073
277 V	1P+N+G	33-14045	33-18045
277 480 V	3P+N+G	33-14047	33-18047
347 600 V	3P+N+G	33-14147	33-18147
480 V	2P+G	33-14042	33-18042
480 V	3P+G	33-14043	33-18043
600 V	2P+G	33-14142	33-18142
600 V	3P+G	33-14143	33-18143

For international configurations and ratings (IEC,CE) visit meltric.com/international-catalog or contact Customer Service at 800-433-7642.

Main Options



**Auxiliary/Pilot
Contacts**



**Mushroom
Pawl**



Padlock Pawl



**Closed Lid
Configuration**

Recommended for cord
applications to keep lid
tucked in to avoid damage.

Receptacle Options

Suffix

Inlet Options

Suffix

With 2 Auxiliary/Pilot Contacts	Recept # -972	With 2 Auxiliary/Pilot Contacts	Inlet # -972
Type 4X & Closed Lid Configuration	Recept # -4X	Type 4X Watertightness	Inlet # -4X
Straight Insertion	Recept # -352~	Self-Ejecting Plug Release**	Inlet # -338
Self-Ejecting Connector Release**	Recept # -354~	With No Lockout Hole	Inlet # -A155
Mushroom Pawl	Recept # -375	For Auxiliary Switch	Inlet # -270+
Padlock Pawl	Recept # -843		
Padlockable Mushroom Pawl	Recept # -375-843		
Screw-Type Locking Pawl	Recept # -845		
Metal Pawl (on Poly Receptacle)	Recept # -824		
Closed Lid Configuration	Recept # -NC		
With Auxiliary Switch	Recept # -270+		

Notes: + Not UL/CSA listed.

** For self-ejecting connectors and plugs, a -443 suffix must be added to the handle part number. See pages 251-252 for more information.

~ Standard closed lid configuration.

! See pages 243-252 for detailed information on these options


Order Example: 208 V DS20 + 2 auxiliary contacts

DS20 Poly inlet 2P+G = 33-18162-972


INSTALLATION ACCESSORIES – SIZE 2


Accessories can be used with either poly or metal plugs and receptacles.

HANDLES


HANDLE w/NPT	Part # Poly	Part # Metal
 Poly 1/2"	512P0N05	592P0N05
3/4"	512P0N07	592P0N07
1"	512P0N10	592P0N10
1 1/4"	512P0N12	-

For available cord grips, see page 169. Add -443 for self-ejecting.


POLY HANDLE w/CORD GRIP	Cable Range	Part #
	.350 - .520"	712P0BP6
	.520 - .680"	712P0CP5
	.680 - .980"	712P0DP4
	.980 - 1.260"	712P0EP4

METAL HANDLE w/CORD GRIP	Cable Range	Part #
	.438 - .500"	792P0BS3
	.500 - .562"	792P0BS4
	.562 - .625"	792P0CS2
	.625 - .750"	792P0CS4
	.750 - .875"	792P0DS1
	.875 - 1.000"	792P0DS3


POLY HANDLE	Cable Range	Part #
	.20 - .82"	512P0D21


POLY HANDLE w/CLAMP & BUSHING	Cable Range	Part #
	.750 - .875"	712P0S14
	.875 - 1.000"	712P0S16
	1.000 - 1.125"	712P0S18
	1.125 - 1.250"	712P0S20
	1.250 - 1.375"	712P0S22


ANGLES

POLY ANGLE	Angle	Part #	Notes
	30°	512M3	


POLY ANGLE	Angle	Part #	Notes
	70°	512M7	Panel mounting only.

METAL ANGLE	Angle	Part #
	0°	592M0

METAL ANGLE	Angle	Part #
	30°	592M3


METAL ANGLE	Angle	Part #	Notes
	FS/FD Box 30°	792M3FS	* Base measures approximately 4.2" x 2.7". Due to the variation in sizes of FS boxes, please verify that your FS box matches our dimensions, if not call Customer Service for other solutions.


BOXES


POLY CONDUIT ENTRY w/NPT	Angle	Size	Part #	Notes
	30°	1/2"	512B3N05	For poly devices only
	30°	3/4"	512B3N07	* Interior volume with receptacle installed.

POLY WALL BOX w/ANGLE	Angle	Part #	Notes
	70°	512C7000	70° poly boxes are not drilled. Contact Customer Service if factory drilling is required.

GROUND BAR	Part #	Notes
	51AA089	* Interior volume with receptacle installed.


POLY ANGLE WITH METAL BOX w/NPT	Angle	Size	Part #	Notes
	70°	1/2"	712C7N05	
	70°	3/4"	712C7N07	
	70°	1"	712C7N10	* Interior volume with receptacle installed.
	70°	1 1/4"	712C7N12	
	70°	1 1/2"	712C7N15	

METAL BOX w/NPT	Angle	Size	Part #
	0°	1/2"	7T1F0N05
	0°	3/4"	7T1F0N07
	0°	1"	7T1F0N10
	0°	1 1/4"	7T1F0N12

POLY ANGLE WITH METAL BOX w/NPT	Angle	Size	Part #	Notes
	30°	1/2"	712C3N05	
	30°	3/4"	712C3N07	* Interior volume with receptacle installed.
	30°	1"	712C3N10	
	30°	1 1/4"	712C3N12	

NPT on top or bottom (if rotated). For other NPT configurations, contact Customer Service.

MISCELLANEOUS ACCESSORIES

FINGER DRAWPLATES	Part #	Notes
	61-3A346	Set of Two (2) Recommended for cord to cord assembly applications, for easier connector closure.

PROTECTIVE INLET/PLUG CAP	Part #	Notes
	31-1A426	For Inlets/Plugs Only.

PADLOCKABLE INLET/PLUG CAP	Part #	Notes
	DS1PC	For Inlets/Plugs Only.

SPRING-LOADED PADLOCKABLE INLET/PLUG CAP	Part #	Notes
	31-1A226	For Inlets/Plugs Only. -A155 suffix required to maintain water ingress protection.

EASY RETROFIT ADAPTER PLATES	Part #	Notes
	see pg 166	Mount to existing boxes.

RECEPTACLE LOCKING PIN	Part #	Notes
	LP-843	Requires Padlockable Pawl option (-843) on receptacle.