

UL/CSA RATINGS

- Max Amperage & Voltage**
60 A, 600 VAC
- Switch-Rating (AC Only)**
Branch Circuit & Motor Circuit Disconnect Switching
- Horsepower Ratings**

120 V	1Ø	2 hp
240 V	1Ø	3 hp
208 V	3Ø	7.5 hp
240 V	3Ø	7.5 hp
480 V	3Ø	20 hp
600 V	3Ø	20 hp
- Short Circuit Rating**
100 kA Close & Withstand
Testing was performed with RKT current limiting fuses sized at 400% of the highest full load motor ampacity associated with the devices hp rating.
- Environmental Ratings**
Type 4X/IP66/IP67/IP69/IP69K
- Temperature Range**
Min -40°F/Max 140°F
See pg 254 for temperatures outside of this range.
- Wiring Capacity**
Based on THHN wire sizes
Min 14 AWG Max 4 AWG
Aux Contacts - 14 AWG
- Certifications**
UL 2682, UL 1682,
CSA C22.2 NO. 182.1, NOM

Receptacle (female)



Inlet (male)



! Don't forget to add installation accessories to your order

North American UL/CSA Configurations

VOLTAGE	POLARITY	PART # POLY	PART # POLY
120 V	1P+N+G	63-64165	63-68165
120 208 V	3P+N+G	63-64167	63-68167
125 V	1P+N+G	63-64075	63-68075
125 250 V	2P+N+G	63-64076	63-68076
208 V	2P+G	63-64162	63-68162
208 V	3P+G	63-64163	63-68163
250 V	2P+G	63-64072	63-68072
250 V	3P+G	63-64073	63-68073
277 V	1P+N+G	63-64045	63-68045
277 480 V	3P+N+G	63-64047	63-68047
347 600 V	3P+N+G	63-64147	63-68147
480 V	2P+G	63-64042	63-68042
480 V	3P+G	63-64043	63-68043
600 V	2P+G	63-64142	63-68142
600 V	3P+G	63-64143	63-68143

For international configurations and ratings (IEC,CE) visit meltric.com/international-catalog or contact Customer Service at 800-433-7642.

MAIN OPTIONS

- Auxiliary/Pilot Contacts**
- Mushroom Pawl**
- Padlock Pawl**
5/16" hole
- Self-Returning Lid**
Recommended for cord applications to keep lid tucked in to avoid damage.

RECEPTACLE OPTIONS

RECEPTACLE OPTIONS	SUFFIX #	INLET OPTIONS	SUFFIX #
With 2 Auxiliary/Pilot Contacts	Recept # -972	With 2 Auxiliary/Pilot Contacts	Inlet # -972
With 3 Auxiliary/Pilot Contacts	Recept # -973	With 3 Auxiliary/Pilot Contacts	Inlet # -973
With 4 Auxiliary/Pilot Contacts	Recept # -974	With 4 Auxiliary/Pilot Contacts	Inlet # -974
Straight Insertion	Recept # -352 ²	Self-Ejecting Plug Release**	Inlet # -338
Self-Ejecting Connector Release**	Recept # -354 ²	Without Lockout Hole	Inlet # -A155
Mushroom Pawl	Recept # -375	For Microswitch	Inlet # -270 ^{3,4}
Padlock Pawl	Recept # -843		
Padlockable Mushroom Pawl	Recept # -375		
Metal Pawl	Recept # -824		
Self-Returning Lid (Manual Close)	Recept # -NC		
With Microswitch	Recept # -270 ^{3,4}		

Notes:
 ** For self-ejecting connectors and plugs, a 443 suffix must be added to the handle part number. See pages 233-234 for more information.
² This option includes the Self-Returning Lid.
³ Not UL/CSA listed.
⁴ Not available on 3P+N+G configurations

Order Example: 480 V DSN60 + 2 auxiliary contacts
DSN60 Inlet 3P+G = 63-68043-972



Handle Option Guide
pgs 237-238

INSTALLATION ACCESSORIES – SIZE 3

When properly installed, all accessories meet or exceed the environmental ratings of the devices they are mounted to; unless otherwise noted.

HANDLES

HANDLE WITH NPT	PART # POLY	PART # METAL
Poly 1/2"	513P0N05	593P0N05
Poly 3/4"	513P0N07	593P0N07
Metal 1"	513P0N10	593P0N10
Metal 1 1/4"	513P0N12	593P0N12

For available cord grips, see pg 159.

POLY HANDLE WITH CORD GRIP	CABLE RANGE	PART #
	.520-.680"	713P0CP5
	.680-.980"	713P0DP4
	.980-1.260"	713P0EP4

METAL HANDLE WITH CORD GRIP	CABLE RANGE	PART #
	.635-.750"	793P0CS4
	.770-.850"	793P0DS1
	.875-1.000"	793P0DS3
	1.000-1.125"	793P0ES2

POLY HANDLE	CABLE RANGE	PART #
	.390-1.180"	513P0D30

POLY HANDLE WITH BUILT IN DRAWPLATES	CABLE RANGE	PART #
	.390-1.180"	513P0D30473

Makes connector closures easier.

POLY HANDLE WITH CLAMP & BUSHING	CABLE RANGE	PART #
	.750-.875"	713P0S14
	.875-1.000"	713P0S16
	1.000-1.125"	713P0S18
	1.125-1.250"	713P0S20
	1.250-1.375"	713P0S22

ANGLES

POLY ANGLE	ANGLE	PART #	Notes
	30°	513M3	
	70°	513M7	Panel mounting only.

METAL ANGLE	ANGLE	PART #	Notes
	0°	593M0	
	30°	593M3	
	FS/FD 30°	793M3FS	Base measures approximately 4.2" x 2.7". Due to the variation in sizes of FS boxes, please verify that your FS box matches our dimensions, if not call Customer Service for other solutions.
	70°	593M7	

BOXES

POLY CONDUIT ENTRY WITH NPT	ANGLE	SIZE	PART #	Notes
	30°	1/2"	513B3N05	* Interior volume with receptacle installed.
	30°	3/4"	513B3N07	
	30°	1"	513B3N10	

POLY WALL BOX WITH ANGLE	ANGLE	PART #	Notes
	70°	513C7000	70° poly boxes are not drilled. * Interior volume with receptacle installed.

POLY ANGLE WITH METAL BOX WITH NPT	ANGLE	SIZE	PART #	Notes
	70°	1/2"	713C7N05	* Interior volume with receptacle installed.
	70°	3/4"	713C7N07	
	70°	1"	713C7N10	
	70°	1 1/4"	713C7N12	
	70°	1 1/2"	713C7N15	

METAL BOX WITH NPT	ANGLE	SIZE	PART #
	0°	1/2"	7T1F0N05
	0°	3/4"	7T1F0N07
	0°	1"	7T1F0N10
	0°	1 1/4"	7T1F0N12

POLY ANGLE WITH METAL BOX WITH NPT	ANGLE	SIZE	PART #	Notes
	30°	1/2"	713C3N05	* Interior volume with receptacle installed.
	30°	3/4"	713C3N07	
	30°	1"	713C3N10	
	30°	1 1/4"	713C3N12	

NPT on top or bottom (if rotated). For other configurations, contact Customer Service.

MISCELLANEOUS ACCESSORIES

FINGER DRAWPLATES	PART #	Notes
	61-6A346	Set of Two (2) Recommended for cord to cord assembly applications, for facilitated mating.

PROTECTIVE INLET/PLUG CAP	PART #	Notes
	61-6A426	For Inlets/Plugs Only.

PADLOCKABLE INLET/PLUG CAP	PART #	Notes
	61-6A826	For Inlets/Plugs Only.

SPRING-LOADED PADLOCKABLE INLET/PLUG CAP	PART #	Notes
	61-6A226	Metal - For Inlets/Plugs Only. In order to achieve max water ingress protection of Type 3R/IP55, spring loaded caps should be ordered with inlets equipped with -A155 suffix.

CORD GRIP WITH OPTIONS	Notes
	see pg 159

RECEPTACLE LOCKING PIN	PART #	Notes
	LP-843	Requires Padlockable Pawl option (-843) on receptacle.