

DX1 Hazardous Location - 20 A

Ratings

- Max Amperage & Voltage**
20 A, 750 VAC
- Environmental Ratings**
IP65
- Temperature Range**
Min -13°F/Max 140°F
See pg 252 for temperatures outside this range.
- Wiring Capacity**
Min 14 AWG Max 8 AWG
* Based on THHN wire sizes.
- Applicable Standards**
ATEX, IECEx
- Hazardous Location Ratings**
MARECHAL ELECTRIC MAROMME
II2 G/D Ex de IIC tD A21
-25°C ≤ Ta ≤ +60°C T5 T84°C
-25°C ≤ Ta ≤ +50°C T6 T74°C
IECEx LCI 09.0014/LCIE 05 ATEX 6127

Handle Cable Range

SUFFIX	CABLE RANGE SIZE
None	.31" - .51"
-25M	.35" - .63"
-32M	.47" - .83"

Box Size

SUFFIX	NPT THREAD SIZE
-12	1/2"
-34	3/4"
None	1"

NPT sizes are determined by the cable diameter and third party cord grip.

Accessories

PROTECTIVE CAP



For Male Devices Only

DX1 26-2A126

METAL WALL BOX



NPT	PART #
1/2"	26-2A023-12
3/4"	26-2A023-34
1"	26-2A023-1

Devices rated for hazardous locations are not returnable.

Plug
(male inlet w/handle)



Inlet w/Cap on Box
(male)



or

North American Configurations

VOLTAGE	POLARITY	PART # METAL	PART # METAL
120 V	1P+N+G	26-21165	26-26165
125 V	1P+N+G	26-21075	26-26075
208 V	2P+G	26-21162	26-26162
208 V	3P+G	26-21163	26-26163
208 V	3P+N+G	26-21167	26-26167
250 V	2P+G	26-21072	26-26072
250 V	3P+G	26-21073	26-26073
250 V	2P+N+G	26-21076	26-26076
277 V	1P+N+G	26-21045	26-26045
480 V	2P+G	26-21042	26-26042
480 V	3P+G	26-21043	26-26043
480 V	3P+N+G	26-21047	26-26047
600 V	3P+G	26-21143	26-26143

For international configurations (IEC/CE) visit meltric.com/international-catalog or contact Customer Service at 800-433-7642.

Connector
(female recept w/handle)



Receptacle on Box
(female)



Receptacle
(female)



or

or

North American Configurations

VOLTAGE	POLARITY	PART # METAL	PART # METAL	PART # METAL
120 V	1P+N+G	26-23165	26-20165	26-24165
125 V	1P+N+G	26-23075	26-20075	26-24075
208 V	2P+G	26-23162	26-20162	26-24162
208 V	3P+G	26-23163	26-20163	26-24163
208 V	3P+N+G	26-23167	26-20167	26-24167
250 V	2P+G	26-23072	26-20072	26-24072
250 V	3P+G	26-23073	26-20073	26-24073
250 V	2P+N+G	26-23076	26-20076	26-24076
277 V	1P+N+G	26-23045	26-20045	26-24045
480 V	2P+G	26-23042	26-20042	26-24042
480 V	3P+G	26-23043	26-20043	26-24043
480 V	3P+N+G	26-23047	26-20047	26-24047
600 V	3P+G	26-23143	26-20143	26-24143

For international configurations (IEC/CE) visit meltric.com/international-catalog or contact Customer Service at 800-433-7642.