

DX1 Hazardous Location Plugs & Receptacles – 20 A

Devices rated for hazardous locations are not returnable.

Ratings

- **Max Amperage & Voltage**
20 A, 750 VAC
- **Environmental Ratings**
IP65
- **Temperature Range**
Min -13°F/Max 140°F
See pg 266 for temps below -15°F.
- **Wiring Capacity**
Min 14 AWG Max 8 AWG
* Based on THHN wire sizes.
- **Applicable Standards**
ATEX, IECEx
- **Hazardous Location Ratings**

MARECHAL ELECTRIC MAROMME
II2 G/D Ex de IIC tD A21
-25°C ≤ Ta ≤ +60°C T5 T84°C
-25°C ≤ Ta ≤ +50°C T6 T74°C
IECEx LCI 09.0014/LCIE 05 ATEX 6127

Handle Cable Range

| Suffix | Cable Range Size |
|--------|------------------|
| None | .31" - .51" |
| -25M | .35" - .63" |
| -32M | .47" - .83" |

Box NPT Size

| Suffix | NPT Thread Size |
|--------|-----------------|
| -12 | 1/2" |
| -34 | 3/4" |
| None | 1" |

NPT sizes are determined by the cable diameter and third party cord grip.

Accessories

Protective Cap



For Male
Devices Only

DX1 26-2A126

Metal Wall Box



| NPT | Part # |
|------|-------------|
| 1/2" | 26-2A023-12 |
| 3/4" | 26-2A023-34 |
| 1" | 26-2A023-1 |

Plug
(Male inlet w/handle)



Inlet w/cap on box
(Male)



or

North American Configurations

| Voltage | Polarity | Part # | |
|---------|----------|----------|----------|
| | | Metal | Metal |
| 120 V | 1P+N+G | 26-21165 | 26-26165 |
| 125 V | 1P+N+G | 26-21075 | 26-26075 |
| 208 V | 2P+G | 26-21162 | 26-26162 |
| 208 V | 3P+G | 26-21163 | 26-26163 |
| 208 V | 3P+N+G | 26-21167 | 26-26167 |
| 250 V | 2P+G | 26-21072 | 26-26072 |
| 250 V | 3P+G | 26-21073 | 26-26073 |
| 250 V | 2P+N+G | 26-21076 | 26-26076 |
| 277 V | 1P+N+G | 26-21045 | 26-26045 |
| 480 V | 2P+G | 26-21042 | 26-26042 |
| 480 V | 3P+G | 26-21043 | 26-26043 |
| 480 V | 3P+N+G | 26-21047 | 26-26047 |
| 600 V | 3P+G | 26-21143 | 26-26143 |

For international configurations (IEC/CE) visit meltric.com/international-catalog or contact Customer Service at 800-433-7642.

Connector
(female recept w/handle)



Receptacle on box
(female)



or

Receptacle
(female)



or

North American Configurations

| Voltage | Polarity | Part # | | |
|---------|----------|----------|----------|----------|
| | | Metal | Metal | Metal |
| 120 V | 1P+N+G | 26-23165 | 26-20165 | 26-24165 |
| 125 V | 1P+N+G | 26-23075 | 26-20075 | 26-24075 |
| 208 V | 2P+G | 26-23162 | 26-20162 | 26-24162 |
| 208 V | 3P+G | 26-23163 | 26-20163 | 26-24163 |
| 208 V | 3P+N+G | 26-23167 | 26-20167 | 26-24167 |
| 250 V | 2P+G | 26-23072 | 26-20072 | 26-24072 |
| 250 V | 3P+G | 26-23073 | 26-20073 | 26-24073 |
| 250 V | 2P+N+G | 26-23076 | 26-20076 | 26-24076 |
| 277 V | 1P+N+G | 26-23045 | 26-20045 | 26-24045 |
| 480 V | 2P+G | 26-23042 | 26-20042 | 26-24042 |
| 480 V | 3P+G | 26-23043 | 26-20043 | 26-24043 |
| 480 V | 3P+N+G | 26-23047 | 26-20047 | 26-24047 |
| 600 V | 3P+G | 26-23143 | 26-20143 | 26-24143 |

For international configurations (IEC/CE) visit meltric.com/international-catalog or contact Customer Service at 800-433-7642.