

DX3 Hazardous Location - 32 A

! Devices rated for hazardous locations are not returnable.

Plug (male inlet w/handle) **or** **Inlet w/Cap on Box** (male)



North American Configurations

VOLTAGE	POLARITY	PART # METAL	PART # METAL
120 V	1P+N+G	2631165	2636165
125 V	1P+N+G	2631075	2636075
208 V	2P+G	2631162	2636162
208 V	3P+G	2631163	2636163
208 V	3P+N+G	2631167	2636167
250 V	2P+G	2631072	2636072
250 V	3P+G	2631073	2636073
250 V	2P+N+G	2631076	2636076
277 V	1P+N+G	2631045	2636045
480 V	2P+G	2631042	2636042
480 V	3P+G	2631043	2636043
480 V	3P+N+G	2631047	2636047
600 V	3P+G	2631143	2636143

For international configurations (IEC/CE) visit meltric.com/international-catalog or contact Customer Service at 800-433-7642.

Ratings

- **Max Amperage & Voltage**
32 A, 750 VAC
- **Environmental Ratings**
IP65
- **Temperature Range**
Min -13°F/Max 140°F
See pg 254 for temperatures outside this range.
- **Wiring Capacity**
Based on THHN wire sizes.
Min 14 AWG Max 8 AWG
- **Applicable Standards**
ATEX, IECEx
- **Hazardous Location Ratings**

MARECHAL ELECTRIC MAROMME
II2 G/D Ex de IIC tD A21
-25°C ≤ Ta ≤ +60°C T5 T84°C
-25°C ≤ Ta ≤ +50°C T6 T74°C
IECEx LCI 09.0014/LCIE 05 ATEX 6127

Handle Cable Range

SUFFIX	CABLE RANGE SIZE
-20M	.31" - .51"
None	.35" - .63"
-32M	.47" - .83"


Box Size

SUFFIX	NPT THREAD SIZE
-12	1/2"
-34	3/4"
None	1"

NPT sizes are determined by the cable diameter and third party cord grip.

Accessories

PROTECTIVE CAP



METAL WALL BOX

NPT	PART #
1/2"	263A02312
3/4"	263A02334
1"	263A0231

Connector (female recept w/handle) **or** **Receptacle on Box** (female) **or** **Receptacle** (female)



North American Configurations

VOLTAGE	POLARITY	PART # METAL	PART # METAL	PART # METAL
120 V	1P+N+G	2633165	2630165	2634165
125 V	1P+N+G	2633075	2630075	2634075
208 V	2P+G	2633162	2630162	2634162
208 V	3P+G	2633163	2630163	2634163
208 V	3P+N+G	2633167	2630167	2634167
250 V	2P+G	2633072	2630072	2634072
250 V	3P+G	2633073	2630073	2634073
250 V	2P+N+G	2633076	2630076	2634076
277 V	1P+N+G	2633045	2630045	2634045
480 V	2P+G	2633042	2630042	2634042
480 V	3P+G	2633043	2630043	2634043
480 V	3P+N+G	2633047	2630047	2634047
600 V	3P+G	2633143	2630143	2634143

For international configurations (IEC/CE) visit meltric.com/international-catalog or contact Customer Service at 800-433-7642.