

DX3 Hazardous Location Plugs & Receptacles – 32 A

Devices rated for hazardous locations are not returnable.

Plug
(Male inlet w/handle)

or

Inlet w/cap on box
(Male)



North American Configurations

| Voltage | Polarity | Part # Metal | Part # Metal |
|---------|----------|-----------------|-----------------|
| 120 V | 1P+N+G | 26-31165 | 26-36165 |
| 125 V | 1P+N+G | 26-31075 | 26-36075 |
| 208 V | 2P+G | 26-31162 | 26-36162 |
| 208 V | 3P+G | 26-31163 | 26-36163 |
| 208 V | 3P+N+G | 26-31167 | 26-36167 |
| 250 V | 2P+G | 26-31072 | 26-36072 |
| 250 V | 3P+G | 26-31073 | 26-36073 |
| 250 V | 2P+N+G | 26-31076 | 26-36076 |
| 277 V | 1P+N+G | 26-31045 | 26-36045 |
| 480 V | 2P+G | 26-31042 | 26-36042 |
| 480 V | 3P+G | 26-31043 | 26-36043 |
| 480 V | 3P+N+G | 26-31047 | 26-36047 |
| 600 V | 3P+G | 26-31143 | 26-36143 |

For international configurations (IEC/CE) visit meltric.com/international-catalog or contact Customer Service at 800-433-7642.

Connector
(female recept w/handle)

Receptacle on box
(female)

Receptacle
(female)



or



or



North American Configurations

| Voltage | Polarity | Part # Metal | Part # Metal | Part # Metal |
|---------|----------|-----------------|-----------------|-----------------|
| 120 V | 1P+N+G | 26-33165 | 26-30165 | 26-34165 |
| 125 V | 1P+N+G | 26-33075 | 26-30075 | 26-34075 |
| 208 V | 2P+G | 26-33162 | 26-30162 | 26-34162 |
| 208 V | 3P+G | 26-33163 | 26-30163 | 26-34163 |
| 208 V | 3P+N+G | 26-33167 | 26-30167 | 26-34167 |
| 250 V | 2P+G | 26-33072 | 26-30072 | 26-34072 |
| 250 V | 3P+G | 26-33073 | 26-30073 | 26-34073 |
| 250 V | 2P+N+G | 26-33076 | 26-30076 | 26-34076 |
| 277 V | 1P+N+G | 26-33045 | 26-30045 | 26-34045 |
| 480 V | 2P+G | 26-33042 | 26-30042 | 26-34042 |
| 480 V | 3P+G | 26-33043 | 26-30043 | 26-34043 |
| 480 V | 3P+N+G | 26-33047 | 26-30047 | 26-34047 |
| 600 V | 3P+G | 26-33143 | 26-30143 | 26-34143 |

For international configurations (IEC/CE) visit meltric.com/international-catalog or contact Customer Service at 800-433-7642.

Ratings

- **Max Amperage & Voltage**
32 A, 750 VAC
- **Environmental Ratings**
IP65
- **Temperature Range**
Min -13°F/Max 140°F
See pg 266 for temps below -15°F.
- **Wiring Capacity**
Min 14 AWG Max 8 AWG
* Based on THHN wire sizes.
- **Applicable Standards**
ATEX, IECEx
- **Hazardous Location Ratings**

MARECHAL ELECTRIC MAROMME
II2 G/D Ex de IIC tD A21
-25°C ≤ Ta ≤ +60°C T5 T84°C
-25°C ≤ Ta ≤ +50°C T6 T74°C
IECEx LCI 09.0014/LCIE 05 ATEX 6127

Handle Cable Range

| Suffix | Cable Range Size |
|--------|------------------|
| -20M | .31" - .51" |
| None | .35" - .63" |
| -32M | .47" - .83" |

Box NPT Size

| Suffix | NPT Thread Size |
|--------|-----------------|
| -12 | 1/2" |
| -34 | 3/4" |
| None | 1" |

NPT sizes are determined by the cable diameter and third party cord grip.

Accessories

Protective Cap



For Male Devices Only

DX3 26-3A126

Metal Wall Box



| NPT | Part # |
|------|-------------|
| 1/2" | 26-3A023-12 |
| 3/4" | 26-3A023-34 |
| 1" | 26-3A023-1 |

HAZARDOUS LOCATION