

# DX3 Hazardous Location - 32 A

**!** Devices rated for hazardous locations are not returnable.

**Plug**  
(male inlet w/handle)



or

**Inlet w/Cap on Box**  
(male)



## North American Configurations

VOLTAGE	POLARITY	PART # METAL	PART # METAL
120 V	1P+N+G	26-31165	26-36165
125 V	1P+N+G	26-31075	26-36075
208 V	2P+G	26-31162	26-36162
208 V	3P+G	26-31163	26-36163
208 V	3P+N+G	26-31167	26-36167
250 V	2P+G	26-31072	26-36072
250 V	3P+G	26-31073	26-36073
250 V	2P+N+G	26-31076	26-36076
277 V	1P+N+G	26-31045	26-36045
480 V	2P+G	26-31042	26-36042
480 V	3P+G	26-31043	26-36043
480 V	3P+N+G	26-31047	26-36047
600 V	3P+G	26-31143	26-36143

For international configurations (IEC/CE) visit [meltric.com/international-catalog](http://meltric.com/international-catalog) or contact Customer Service at 800-433-7642.

## Ratings

- **Max Amperage & Voltage**  
32 A, 750 VAC
- **Environmental Ratings**  
IP65
- **Temperature Range**  
Min -13°F/Max 140°F  
See pg 252 for temperatures outside this range.
- **Wiring Capacity**  
Min 14 AWG Max 8 AWG  
\* Based on THHN wire sizes.
- **Applicable Standards**  
ATEX, IECEx
- **Hazardous Location Ratings**

MARECHAL ELECTRIC MAROMME  
II2 G/D Ex de IIC tD A21  
-25°C ≤ Ta ≤ +60°C T5 T84°C  
-25°C ≤ Ta ≤ +50°C T6 T74°C  
IECEX LCI 09.0014/LCIE 05 ATEX 6127

## Handle Cable Range

SUFFIX	CABLE RANGE SIZE
-20M	.31" - .51"
None	.35" - .63"
-32M	.47" - .83"


## Box Size

SUFFIX	NPT THREAD SIZE
-12	1/2"
-34	3/4"
None	1"

NPT sizes are determined by the cable diameter and third party cord grip.

## Accessories

### PROTECTIVE CAP



### METAL WALL BOX

NPT	PART #
1/2"	26-3A023-12
3/4"	26-3A023-34
1"	26-3A023-1

**Connector**  
(female recept w/handle)



or

**Receptacle on Box**  
(female)



or

**Receptacle**  
(female)



## North American Configurations

VOLTAGE	POLARITY	PART # METAL	PART # METAL	PART # METAL
120 V	1P+N+G	26-33165	26-30165	26-34165
125 V	1P+N+G	26-33075	26-30075	26-34075
208 V	2P+G	26-33162	26-30162	26-34162
208 V	3P+G	26-33163	26-30163	26-34163
208 V	3P+N+G	26-33167	26-30167	26-34167
250 V	2P+G	26-33072	26-30072	26-34072
250 V	3P+G	26-33073	26-30073	26-34073
250 V	2P+N+G	26-33076	26-30076	26-34076
277 V	1P+N+G	26-33045	26-30045	26-34045
480 V	2P+G	26-33042	26-30042	26-34042
480 V	3P+G	26-33043	26-30043	26-34043
480 V	3P+N+G	26-33047	26-30047	26-34047
600 V	3P+G	26-33143	26-30143	26-34143

For international configurations (IEC/CE) visit [meltric.com/international-catalog](http://meltric.com/international-catalog) or contact Customer Service at 800-433-7642.