

DX6 Hazardous Location Plugs & Receptacles – 63 A

Devices rated for hazardous locations are not returnable.

Ratings

- **Max Amperage & Voltage**
63 A, 750 VAC
- **Environmental Ratings**
IP65/IP66
- **Temperature Range**
Min -40°F / Max 140°F
See pg 266 for temps below -15°F.
- **Wiring Capacity**
Min 6 AWG Max 1/0 AWG
* Based on THHN wire sizes.
- **Applicable Standards**
ATEX, IECEx
- **Hazardous Location Ratings**

MARECHAL ELECTRIC MAROMME
II 2 G/D Ex de IIC tD A21
-40°C ≤ Ta ≤ +60°C T5 T90°C
-40°C ≤ Ta ≤ +50°C T6 T80°C
IECEx LCI 09.0015/LCIE 04 ATEX 6038

Handle Cable Range

Suffix	Cable Range Size
None	.47" - .83"
-40M	.63" - 1.06"
-50M	.91" - 1.38"
-63M	1.42 - 1.89"

Box NPT Size

Suffix	NPT Thread Size
-1	1"
None	1 1/4"
-112	1 1/2"
-2	2"

NPT sizes are determined by the cable diameter and third party cord grip.

Accessories

Protective Cap



For Male
Devices Only

DX6 26-6A126

Metal Wall Box



NPT	Part #
1"	26-6A023-1
1 1/4"	26-6A023-114
1 1/2"	26-6A023-112
2"	26-6A023-2

Plug
(Male inlet w/handle)



Inlet w/cap on box
(Male)



or

North American Configurations

Voltage	Polarity	Part # Metal	Part # Metal
120 V	1P+N+G	26-61165	26-66165
125 V	1P+N+G	26-61075	26-66075
208 V	2P+G	26-61162	26-66162
208 V	3P+G	26-61163	26-66163
208 V	3P+N+G	26-61167	26-66167
250 V	2P+G	26-61072	26-66072
250 V	3P+G	26-61073	26-66073
250 V	2P+N+G	26-61076	26-66076
277 V	1P+N+G	26-61045	26-66045
480 V	2P+G	26-61042	26-66042
480 V	3P+G	26-61043	26-66043
480 V	3P+N+G	26-61047	26-66047
600 V	3P+G	26-61143	26-66143

For international configurations (IEC/CE) visit meltric.com/international-catalog or contact Customer Service at 800-433-7642.

Connector
(female recept w/handle)



Receptacle on box
(female)



Receptacle
(female)



or

or

North American Configurations

Voltage	Polarity	Part # Metal	Part # Metal	Part # Metal
120 V	1P+N+G	26-63165	26-60165	26-64165
125 V	1P+N+G	26-63075	26-60075	26-64075
208 V	2P+G	26-63162	26-60162	26-64162
208 V	3P+G	26-63163	26-60163	26-64163
208 V	3P+N+G	26-63167	26-60167	26-64167
250 V	2P+G	26-63072	26-60072	26-64072
250 V	3P+G	26-63073	26-60073	26-64073
250 V	2P+N+G	26-63076	26-60076	26-64076
277 V	1P+N+G	26-63045	26-60045	26-64045
480 V	2P+G	26-63042	26-60042	26-64042
480 V	3P+G	26-63043	26-60043	26-64043
480 V	3P+N+G	26-63047	26-60047	26-64047
600 V	3P+G	26-63143	26-60143	26-64143

For international configurations (IEC/CE) visit meltric.com/international-catalog or contact Customer Service at 800-433-7642.