

DX9 Hazardous Location Plugs & Receptacles – 125 A

Devices rated for hazardous locations are not returnable.

Plug
(Male inlet w/handle) **Inlet w/cap on box**
(Male)



North American Configurations

| Voltage | Polarity | Part # Metal | Part # Metal |
|---------|----------|-----------------|-----------------|
| 120 V | 1P+N+G | 26-91165 | 26-96165 |
| 125 V | 1P+N+G | 26-91075 | 26-96075 |
| 208 V | 2P+G | 26-91162 | 26-96162 |
| 208 V | 3P+G | 26-91163 | 26-96163 |
| 208 V | 3P+N+G | 26-91167 | 26-96167 |
| 250 V | 2P+G | 26-91072 | 26-96072 |
| 250 V | 3P+G | 26-91073 | 26-96073 |
| 250 V | 2P+N+G | 26-91076 | 26-96076 |
| 277 V | 1P+N+G | 26-91045 | 26-96045 |
| 480 V | 2P+G | 26-91042 | 26-96042 |
| 480 V | 3P+G | 26-91043- | 26-96043 |
| 480 V | 3P+N+G | 26-91047 | 26-96047 |
| 600 V | 3P+G | 26-91143 | 26-96143 |

For international configurations (IEC/CE) visit meltric.com/international-catalog or contact Customer Service at 800-433-7642.

Ratings

- **Max Amperage & Voltage**
125 A, 750 VAC
- **Environmental Ratings**
IP65/IP66
- **Temperature Range**
Min -40°F / Max 140°F
See pg 266 for temps below -15°F.
- **Wiring Capacity**
Min 2 AWG Max 2/0 AWG
* Based on THHN wire sizes.
- **Applicable Standards**
ATEX, IECEx
- **Hazardous Location Ratings**

MARECHAL ELECTRIC MAROMME
II2 G/D Ex de IIC tD A21
-40°C ≤ Ta ≤ +60°C T5 T90°C
-40°C ≤ Ta ≤ +50°C T6 T80°C
IECEx LCI 09.0015/LCIE 04 ATEX 6038

Handle Cable Range

| Suffix | Cable Range Size |
|--------|------------------|
| -32M | .47" - .83" |
| None | .63" - 1.06" |
| -50M | .91" - 1.38" |
| -63M | 1.42" - 1.89" |

Box NPT Size

| Suffix | NPT Thread Size |
|--------|-----------------|
| -1 | 1" |
| None | 1 1/4" |
| -112 | 1 1/2" |
| -2 | 2" |

NPT sizes are determined by the cable diameter and third party cord grip.

Accessories

Protective Cap



Metal Wall Box

| NPT | Part # |
|--------|--------------|
| 1" | 26-9A023-1 |
| 1 1/4" | 26-9A023-114 |
| 1 1/2" | 26-9A023-112 |
| 2" | 26-9A023-2 |

Connector **Receptacle on box** **Receptacle**
(female recept w/handle) (female) (female)



North American Configurations

| Voltage | Polarity | Part # Metal | Part # Metal | Part # Metal |
|---------|----------|-----------------|-----------------|-----------------|
| 120 V | 1P+N+G | 26-93165 | 26-90165 | 26-94165 |
| 125 V | 1P+N+G | 26-93075 | 26-90075 | 26-94075 |
| 208 V | 2P+G | 26-93162 | 26-90162 | 26-94162 |
| 208 V | 3P+G | 26-93163 | 26-90163 | 26-94163 |
| 208 V | 3P+N+G | 26-93167 | 26-90167 | 26-94167 |
| 250 V | 2P+G | 26-93072 | 26-90072 | 26-94072 |
| 250 V | 3P+G | 26-93073 | 26-90073 | 26-94073 |
| 250 V | 2P+N+G | 26-93076 | 26-90076 | 26-94076 |
| 277 V | 1P+N+G | 26-93045 | 26-90045 | 26-94045 |
| 480 V | 2P+G | 26-93042 | 26-90042 | 26-94042 |
| 480 V | 3P+G | 26-93043 | 26-90043 | 26-94043 |
| 480 V | 3P+N+G | 26-93047 | 26-90047 | 26-94047 |
| 600 V | 3P+G | 26-93143 | 26-90143 | 26-94143 |

For international configurations (IEC/CE) visit meltric.com/international-catalog or contact Customer Service at 800-433-7642.