



- **Introduction**

- **MELTRIC Overview**

pg 3

- **Product Features & Benefits**

pg 5

- **Part Number & Ordering Guide**

pg 9

- **Product Summary & Selection Guide**

pg 11



- **Switch-Rated Plugs & Receptacles**

- **The Main Differences**

pg 17

- **Selection Guide**

pg 21

- **DSN**

- Type 4X/IP69/IP69K rated, metal or poly casings. From 20-150 A (3/4-75 hp)

- **DS**

- Type 3R rated (4X option), metal, or poly casings. From 20-200 A (3/4-100 hp)

pg 41



- **Multipin Plugs and Receptacles**

- **Multipin**

- 6-37 pin connectors in poly and metal. From 2 - 50 A

pg 57



- **RETTBOX® S**

- **Electromagnetic Self-Ejection**

- 20 - 30 A

pg 83



- **Standard Duty Plugs & Receptacles**

- **DR**

- Type 3R rated (4X option), poly, or metal casings. From 30 - 400 A

pg 89

- **PN**

- P66/IP67 rated or IP55 rated, poly, or metal. 20 A

pg 105

- **PNHT**

- For environments up to 465° F (240°C)

pg 113

- **DSDC**

- DC current rated, poly, or metal casings. From 20 - 200 A (up to 750 VDC)

pg 117



- **High Ampacity Plugs & Receptacles**

- **PF/PFQ**

- IP66/IP67 rated, metal construction. From 300 - 600 A

pg 123

- **DR400**

- Type 3R rated, metal casings. 400 A

pg 131

- **CS1000**

- Single pole, connectors up to 400 A

pg 135

- **SP**

- Single Pole, connectors up to 600 A

pg 139

- **DSP400**

- Single Pole plus contacts

pg 143





- **Power Distribution**

- **Custom Power Distribution Solutions**

pg 151

- **Rubber Power Distribution Boxes**

pg 153

- **Disconnect Combinations**

pg 155

- **Specialty Products**

- **Cord Grips**

pg 159

- **Phase Rotation/Voltage Indicator Assemblies**

pg 161



- **Hazardous Location Plugs & Receptacles**

- **Hazardous Duty Selection Guide**

pg 166

- **DXN**

- Hazardous rated, poly casings. From 20 - 60 A (3/4-20 hp)

pg 167

- **DXA1**

- Hazardous rated, metallic casings. 20 A

pg 179

- **Zone 2 DSN/DS/DR/DSDC**

- Hazardous rated, metallic, or poly casings. 2-250 A (up to 100 hp)

pg 183

- **DX**

- Hazardous rated, metallic casings. From 20-125 A

pg 205

- **PNCX**

- Hazardous rated, poly casings. From 5 A

pg 215

- **Multipin**

- Hazardous rated, 12 to 37 pins. 10 A

pg 217

- **SPeX**

- Hazardous rated, up to 680 A, 1000 VAC

pg 223



- **Reference**

- **Accessories/Options**

pg 229

- **Technical Manual/Reference**

pg 239

- **Parts Index**

pg 255

