

DR30 Hazardous Location Plugs & Receptacles – 30 A

Devices rated for hazardous locations are not returnable.

SP US Ratings

- Voltage**
600 VAC
- Current Interruption Capability**
Not for current interrupting
- Short Circuit Rating**
100 kA Withstand
Testing was performed with RK1 current limiting fuses sized at 100% of the device's ampacity rating.
- Environmental Ratings**
Type 4X
- Temperature Range**
Min -40°F/Max 104°F
See pg 266 for temps below -15°F.
- Wiring Capacity**
Min 14 AWG Max 8 AWG
Aux Contacts - Max 14 AWG
Based on THHN wire sizes.
- Applicable Standards**
CSA C22.2 No. 182.1-07
C22.2 No. 213-M1987
- Hazardous Ratings**
Class I, Division 2, Groups ABCD, T6
Class I, Zone 2, IIC

Receptacle (female)



Inlet (male)



Hazardous Location DR30 lid is normally closed

! Don't forget to add installation accessories to your order

Voltage	Polarity	Part # Poly	Part # Poly
120 V	1P+N+G	35-14235-K16-xxx-HAZ	35-18235-K16-xxx-HAZ
120 208 V	3P+N+G	35-14237-K16-xxx-HAZ	35-18237-K16-xxx-HAZ
125 V	1P+N+G	35-14175-K07-xxx-HAZ	35-18175-K07-xxx-HAZ
125 250 V	2P+N+G	35-14176-K07-xxx-HAZ	35-18176-K07-xxx-HAZ
208 V	2P+G	35-14232-K16-xxx-HAZ	35-18232-K16-xxx-HAZ
208 V	3P+G	35-14233-K16-xxx-HAZ	35-18233-K16-xxx-HAZ
250 V	2P+G	35-14172-K07-xxx-HAZ	35-18172-K07-xxx-HAZ
250 V	3P+G	35-14173-K07-xxx-HAZ	35-18173-K07-xxx-HAZ
277 V	1P+N+G	35-14245-K04-xxx-HAZ	35-18245-K04-xxx-HAZ
277 480 V	3P+N+G	35-14247-K04-xxx-HAZ	35-18247-K04-xxx-HAZ
347 600 V	3P+N+G	35-14187-K14-xxx-HAZ	35-18187-K14-xxx-HAZ
480 V	2P+G	35-14242-K04-xxx-HAZ	35-18242-K04-xxx-HAZ
480 V	3P+G	35-14243-K04-xxx-HAZ	35-18243-K04-xxx-HAZ
600 V	2P+G	35-14182-K14-xxx-HAZ	35-18182-K14-xxx-HAZ
600 V	3P+G	35-14183-K14-xxx-HAZ	35-18183-K14-xxx-HAZ

The xxx represents any and all device options; if no options are needed, the xxx suffix should be omitted.

Part Number Example

480 V DR30 + 2 aux contacts

DR30 recept 3P+G = 35-14243-K04-972-HAZ

480 V DR30 with no options

DR30 recept 3P+G = 35-14243-K04-HAZ

Receptacle Options	Suffix #	Inlet Options	Suffix #
With 2 Auxiliary/Pilot Contacts	Recept # -972	With 2 Auxiliary/Pilot Contacts	Inlet # -972
Normally Open Lid Configuration	Recept # -NO	With No Lockout Hole	Inlet # -A155

Feature Spotlight – Screw-Type Locking Pawl

- ! Listing Requirement**
Users must tighten screw to lock the plug in the mated position



Zone 2/Division 2 DR30 receptacles feature a standard screw-type locking pawl. This required feature allows the user to lock the plug to the receptacle by tightening a screw on the pawl.

For added security, a lockout hole is included on the receptacle that enables the user to insert a 5/16" lock or locking pin to prevent the plug from being disconnected or to lock the receptacle lid closed.



5/16" hole for added security

! See pages 243-252 for detailed information on these options


INSTALLATION ACCESSORIES – SIZE 2

Accessories rated for hazardous locations are not returnable.

HANDLES

HANDLE w/NPT		Part # Poly	Part # Metal
	1/2"	552P0N05	5K2P0N05
	3/4"	552P0N07	5K2P0N07
	1"	552P0N10	5K2P0N10
	1 1/4"	552P0N12	-

For available cord grips, see pg 169.


POLY HANDLE w/Cable Range		
	.20 - .82"	552P0D21

i


Cable Range	NPT	Cable Range	NPT
.312 - .625"	1/2"	.660 - 1.000"	1"
.438 - .812"	3/4"	.875 - 1.375"	1 1/4"

NPT sizes are determined by the cable diameter and third party cord grip.


BOXES

POLY ANGLE WITH METAL BOX w/NPT			
	30°	1/2"	752C3N05
	30°	3/4"	752C3N07
	30°	1"	752C3N10
	30°	1 1/4"	752C3N12

* 28.7 in³ * Interior volume with receptacle installed.

METAL ANGLE WITH METAL BOX w/NPT			
	30°	1/2"	7K2C3N05
	30°	3/4"	7K2C3N07
	30°	1"	7K2C3N10
	30°	1 1/4"	7K2C3N12


* 28.7 in³ * Interior volume with receptacle installed.



POLY ANGLE WITH LARGER METAL BOX w/NPT			
	70°	1/2"	752C7N05
	70°	3/4"	752C7N07
	70°	1"	752C7N10
	70°	1 1/4"	752C7N12
	70°	1 1/2"	752C7N15

* 74.6 in³ * Interior volume with receptacle installed.


NPT on top or bottom (if rotated). For other NPT configurations, contact Customer Service.


ANGLES


POLY ANGLE		
	30°	552M3

METAL ANGLE		
	0°	5K2M0
	30°	5K2M3

MISCELLANEOUS ACCESSORIES

FINGER DRAWPLATES		
	61-3A346	Set of Two (2) Recommended for easier connector closure.

PROTECTIVE INLET/PLUG CAP		
	31-1A426	For Inlets/Plugs Only.

RECEPTACLE LOCKING PIN		
	LP-843	

Notes: For Zone 2 DR dimensions refer to DR dimensions on pgs 103-104.