



DSN150 RECEPTACLE

69-94167-375-843

SPECIFICATIONS

150 A
 120/208 VAC
 Type 4X & IP69
 7.5 hp/30 hp

Rated Current (A)	150 A
Rated Voltage (V)	120/208 VAC
Horsepower Rating	7.5 hp/30 hp
Contact Configuration	3P+N+G
Auxiliary Contacts	NO AUX
Ratings Information	SWITCH RATED BRANCH CIRCUIT DISCONNECT SWITCH MOTOR CIRCUIT DISCONNECT SWITCH
Environmental Rating	Type 4X IP 66/67 IP 69
Short Circuit Rating	100 kA - CLOSE & WITHSTAND
Impact Rating	IK10
Material	METAL
Metal Type	ALUMINUM
Product Color	BLUE
Minimum Operating Temperature	-40F -40C
Maximum Operating Temperature	140F 60C
Wiring Capacity - Phase Contacts	4 AWG - 2/0 AWG SCREW TERMINAL
Applicable Standards	UL 1682 UL 2682 cCSAus C22.2 No. 182.1-13
Option(1)	MUSHROOM PAWL
Option(2)	PADLOCK PAWL
Accessory Size	5
Base Drawing Number	69-94xxx.PDF
Catalog	meltric-catalog-dsn150-en.pdf