



DXN20 INLET

22-18125-K16

SPECIFICATIONS

20 A

127 VAC

IP66/IP67

0.75 hp

| | |
|---|---|
| Rated Current (A) | 20 A |
| Rated Voltage (V) | 127 VAC |
| Horsepower Rating | 0.75 hp |
| Contact Configuration | 1P+N+G |
| Ratings Information | CURRENT INTERRUPTING |
| Environmental Rating | IP 66/67 |
| Short Circuit Rating | 25 kA - CLOSE & WITHSTAND |
| Impact Rating | IK09 |
| Material | POLY |
| Product Color | BLACK |
| Minimum Operating Temperature | -40F -40C |
| Maximum Operating Temperature | 140F 60C |
| Wiring Capacity - Phase Contacts | 16 AWG – 10 AWG SCREW TERMINAL |
| Hazardous Ratings | -40C < Ta < +60C Class I Zone1 AEx de IIC T5 Gb -40C < Ta < +60C Zone 21 AEx tD T90C Db Class I Div 2 Gr A,B,C,D Class II Div 2 Gr E,F,G |
| Applicable Standards | cCSAus C22.2 No. 182.1-13 |
| Accessory Size | 1 |
| Base Drawing Number | 22-18xxx.pdf |
| Catalog | meltric-catalog-dxn20-en.pdf |