



# DXN60 RECEPTACLE

22-64167-924

## SPECIFICATIONS

60 A

208 VAC

IP66/IP67

7.5 hp

|   |  |
|---|--|
| <b>Rated Current (A)</b>                | 60 A   |
| <b>Rated Voltage (V)</b>                | 208 VAC  |
| <b>Horsepower Rating</b>                | 7.5 hp   |
| <b>Contact Configuration</b>            | 3P+N+G   |
| <b>Auxiliary Contacts</b>               | NO AUX   |
| <b>Ratings Information</b>              | CURRENT INTERRUPTING   |
| <b>Environmental Rating</b>             | IP 66/67   |
| <b>Short Circuit Rating</b>             | 25 kA - CLOSE & WITHSTAND  |
| <b>Impact Rating</b>                    | IK09   |
| <b>Material</b>                         | POLY   |
| <b>Product Color</b>                    | BLACK  |
| <b>Minimum Operating Temperature</b>    | -40F<br>-40C   |
| <b>Maximum Operating Temperature</b>    | 140F<br>60C  |
| <b>Wiring Capacity - Phase Contacts</b> | 10 AWG – 4 AWG<br>SCREW TERMINAL   |
| <b>Hazardous Ratings</b>                | -40C < Ta < +60C<br>Class I Zone1 AEx de IIC T4 Gb<br>-40C < Ta < +60C<br>Zone 21 AEx tD T100C Db<br>Class I Div 2 Gr A,B,C,D<br>Class II Div 2 Gr E,F,G |
| <b>Applicable Standards</b>             | cCSAus<br>C22.2 No. 182.1-13   |
| <b>Option(1)</b>                        | METAL PAWL (ON POLY RECEPTACLE)  |
| <b>Accessory Size</b>                   | 3  |
| <b>Base Drawing Number</b>              | <a href="#">22-64xxx.pdf</a>   |
| <b>Catalog</b>                          | <a href="#">meltric-catalog-dxn60-en.pdf</a>   |