



# DR50 RECEPTACLE

31-34243-K04-974-4X

## SPECIFICATIONS

50 A

480 VAC

Type 4X

|   |   |
|---|---|
| <b>Rated Current (A)</b>                | 50 A  |
| <b>Rated Voltage (V)</b>                | 480 VAC                                     |
| <b>Contact Configuration</b>            | 3P+G  |
| <b>Auxiliary Contacts</b>               | +4 AUX                                      |
| <b>Ratings Information</b>              | NON-CURRENT INTERRUPTING                    |
| <b>Environmental Rating</b>             | Type 4X<br>IP 66/67                         |
| <b>Short Circuit Rating</b>             | 100 kA - CLOSE & WITHSTAND                  |
| <b>Impact Rating</b>                    | IK09  |
| <b>Material</b>                         | POLY  |
| <b>Product Color</b>                    | BLUE  |
| <b>Minimum Operating Temperature</b>    | -40F<br>-40C                                |
| <b>Maximum Operating Temperature</b>    | 140F<br>60C                                 |
| <b>Wiring Capacity - Phase Contacts</b> | 14 AWG - 4 AWG<br>SCREW TERMINAL            |
| <b>Applicable Standards</b>             | UL 1682<br>cCSAus<br>C22.2 No. 182.1-13     |
| <b>Option(1)</b>                        | TYPE 4X WATERTIGHTNESS                      |
| <b>Accessory Size</b>                   | 3   |
| <b>Base Drawing Number</b>              | <a href="#">31-34xxx-kxx.PDF</a>            |
| <b>Catalog</b>                          | <a href="#">meltric-catalog-dr50-en.pdf</a> |