



# DXN37c CONNECTOR

## 36-C3003-32M

### SPECIFICATIONS

230 VAC

IP66/IP67

<b>Rated Voltage (V)</b>	230 VAC
<b>Contact Configuration</b>	36P+G
<b>Ratings Information</b>	NON-CURRENT INTERRUPTING
<b>Environmental Rating</b>	IP 66/67
<b>Impact Rating</b>	IK09
<b>Material</b>	METAL
<b>Metal Type</b>	ALUMINUM ANODIZED
<b>Product Color</b>	BLACK
<b>Thread Size</b>	M32
<b>Cable Range</b>	.500-.830"
<b>Minimum Operating Temperature</b>	-40F -40C
<b>Maximum Operating Temperature</b>	131F 55C
<b>Wiring Capacity - Phase Contacts</b>	18 AWG - 14 AWG SOLDER/CRIMP TERMINAL
<b>Hazardous Ratings</b>	II2 G D Ex e IIC Gb Ex tb IIIC Db Ex ia or ib IIC T6 Gb
<b>Accessory Size</b>	3
<b>Base Drawing Number</b>	<a href="#">36-C3003-32M.PDF</a>
<b>Catalog</b>	<a href="#">meltric-catalog-dxn25c-dxn37c-en.pdf</a>