



# DS200 RECEPTACLE

37-24143-972-375

## SPECIFICATIONS

200 A  
 600 VAC  
 Type 4X  
 100 hp

<b>Rated Current (A)</b>	200 A
<b>Rated Voltage (V)</b>	600 VAC
<b>Horsepower Rating</b>	100 hp
<b>Contact Configuration</b>	3P+G
<b>Auxiliary Contacts</b>	+2 AUX
<b>Ratings Information</b>	SWITCH RATED BRANCH CIRCUIT DISCONNECT SWITCH MOTOR CIRCUIT DISCONNECT SWITCH
<b>Environmental Rating</b>	Type 4X IP 66/67
<b>Short Circuit Rating</b>	10 kA - CLOSE & WITHSTAND
<b>Impact Rating</b>	IK10
<b>Material</b>	METAL
<b>Metal Type</b>	ALUMINUM
<b>Product Color</b>	BLUE
<b>Minimum Operating Temperature</b>	-40F -40C
<b>Maximum Operating Temperature</b>	140F 60C
<b>Wiring Capacity - Phase Contacts</b>	4 AWG – 4/0 AWG SCREW TERMINAL
<b>Applicable Standards</b>	UL 2682 UL 1682 cCSAus C22.2 No. 182.1-13
<b>Option(1)</b>	MUSHROOM PAWL
<b>Accessory Size</b>	6
<b>Base Drawing Number</b>	<a href="#">37-24xxx.PDF</a>
<b>Catalog</b>	<a href="#">meltric-catalog-ds200-en.pdf</a>