



DS100 RECEPTACLE

37-94076-262-843-NC

SPECIFICATIONS

100 A
 125/250 VAC
 Type 4X
 3 hp/7.5 hp

Rated Current (A)	100 A
Rated Voltage (V)	125/250 VAC
Horsepower Rating	3 hp/7.5 hp
Contact Configuration	2P+N+G
Auxiliary Contacts	+2 AUX
Ratings Information	SWITCH RATED BRANCH CIRCUIT DISCONNECT SWITCH MOTOR CIRCUIT DISCONNECT SWITCH
Environmental Rating	Type 4X IP 66/67
Short Circuit Rating	100 kA - CLOSE & WITHSTAND
Impact Rating	IK10
Material	METAL
Metal Type	ZAMAK
Product Color	BLUE
Minimum Operating Temperature	-40F -40C
Maximum Operating Temperature	140F 60C
Wiring Capacity - Phase Contacts	4 AWG – 2/0 AWG SCREW TERMINAL
Applicable Standards	UL 2682 UL 1682 cCSAus C22.2 No. 182.1-13
Option(1)	PADLOCK PAWL
Option(2)	NORMALLY CLOSED LID
Accessory Size	5
Base Drawing Number	37-94xxx.PDF
Catalog	meltric-catalog-ds100-en.pdf