



# DR100 RECEPTACLE

39-64243-K04-NC

## SPECIFICATIONS

100 A

480 VAC

Type 4X & IP69

|   |  |
|---|--|
| <b>Rated Current (A)</b>                | 100 A  |
| <b>Rated Voltage (V)</b>                | 480 VAC                                      |
| <b>Contact Configuration</b>            | 3P+G   |
| <b>Auxiliary Contacts</b>               | NO AUX                                       |
| <b>Ratings Information</b>              | NON-CURRENT INTERRUPTING                     |
| <b>Environmental Rating</b>             | Type 4X<br>IP 66/67<br>IP 69                 |
| <b>Short Circuit Rating</b>             | 100 kA - CLOSE & WITHSTAND                   |
| <b>Impact Rating</b>                    | IK09   |
| <b>Material</b>                         | METAL  |
| <b>Metal Type</b>                       | ALUMINUM                                     |
| <b>Product Color</b>                    | BLUE   |
| <b>Minimum Operating Temperature</b>    | -40F<br>-40C                                 |
| <b>Maximum Operating Temperature</b>    | 140F<br>60C                                  |
| <b>Wiring Capacity - Phase Contacts</b> | 10 AWG – 2 AWG<br>SCREW TERMINAL             |
| <b>Applicable Standards</b>             | UL 1682<br>cCSAus<br>C22.2 No. 182.1-13      |
| <b>Option(1)</b>                        | NORMALLY CLOSED LID                          |
| <b>Accessory Size</b>                   | 4  |
| <b>Base Drawing Number</b>              | <a href="#">39-64xxx-kxx.PDF</a>             |
| <b>Catalog</b>                          | <a href="#">meltric-catalog-dr100-en.pdf</a> |