



DSN60 RECEPTACLE

63-64043-974-270

SPECIFICATIONS

60 A
 480 VAC
 Type 4X & IP69
 20 hp

| | |
|-----------------------------------------|-------------------------------------------------------------------------------------|
| Rated Current (A) | 60 A |
| Rated Voltage (V) | 480 VAC |
| Horsepower Rating | 20 hp |
| Contact Configuration | 3P+G |
| Auxiliary Contacts | +4 AUX |
| Ratings Information | SWITCH RATED BRANCH CIRCUIT DISCONNECT SWITCH MOTOR CIRCUIT DISCONNECT SWITCH |
| Environmental Rating | Type 4X IP 66/67 IP 69 |
| Short Circuit Rating | 100 kA - CLOSE & WITHSTAND |
| Impact Rating | IK09 |
| Material | POLY |
| Product Color | BLUE |
| Minimum Operating Temperature | -40F -40C |
| Maximum Operating Temperature | 140F 60C |
| Wiring Capacity - Phase Contacts | 14 AWG – 4 AWG SCREW TERMINAL |
| Option(1) | AUXILIARY SWITCH |
| Accessory Size | 3 |
| Base Drawing Number | 63-64xxx.pdf |
| Catalog | meltric-catalog-dsn60-en.pdf |