



# PN20 INLET

09-N8163

## SPECIFICATIONS

20 A

208 VAC

Type 4X

|   |   |
|---|---|
| <b>Rated Current (A)</b>                | 20 A                                      |
| <b>Rated Voltage (V)</b>                | 208 VAC                                   |
| <b>Contact Configuration</b>            | 3P+G                                      |
| <b>Ratings Information</b>              | CURRENT INTERRUPTING                      |
| <b>Environmental Rating</b>             | Type 4X<br>IP 66/67                       |
| <b>Impact Rating</b>                    | IK09                                      |
| <b>Material</b>                         | METAL                                     |
| <b>Metal Type</b>                       | ZAMAK                                     |
| <b>Product Color</b>                    | METAL                                     |
| <b>Minimum Operating Temperature</b>    | -40F<br>-40C                              |
| <b>Maximum Operating Temperature</b>    | 140F<br>60C                               |
| <b>Wiring Capacity - Phase Contacts</b> | 14 AWG - 8 AWG<br>SCREW TERMINAL          |
| <b>Applicable Standards</b>             | UL 1682<br>cCSAus<br>C22.2 No. 182.1-07   |
| <b>Accessory Size</b>                   | 1   |
| <b>Base Drawing Number</b>              | <a href="#">09-n8xxx.pdf</a>              |
| <b>Catalog</b>                          | <a href="#">meltric-catalog-pn-en.pdf</a> |