



# DN20c RECEPTACLE

17-64141-375-843

## SPECIFICATIONS

15 A

480 VAC/130 VDC

IP54/IP55

3 hp

<b>Rated Current (A)</b>	15 A
<b>Rated Voltage (V)</b>	480 VAC/130 VDC
<b>Horsepower Rating</b>	3 hp
<b>Contact Configuration</b>	14P+G
<b>Ratings Information</b>	CURRENT INTERRUPTING
<b>Environmental Rating</b>	IP 54/55
<b>Short Circuit Rating</b>	10 kA - WITHSTAND
<b>Impact Rating</b>	IK09
<b>Material</b>	METAL
<b>Metal Type</b>	ZAMAK
<b>Product Color</b>	BLUE
<b>Minimum Operating Temperature</b>	-40F -40C
<b>Maximum Operating Temperature</b>	140F 60C
<b>Wiring Capacity - Phase Contacts</b>	16 AWG – 10 AWG SCREW TERMINAL
<b>Applicable Standards</b>	cCSAus C22.2 No. 94.2-15
<b>Option(1)</b>	MUSHROOM PAWL
<b>Option(2)</b>	PADLOCK PAWL
<b>Accessory Size</b>	5
<b>Base Drawing Number</b>	<a href="#">17-64xxx.pdf</a>
<b>Catalog</b>	<a href="#">meltric-catalog-dn20c-en.pdf</a>