



# DN20c INLET

17-68101

## SPECIFICATIONS

20 A

480 VAC/130 VDC

IP54/IP55

3 hp

|   |  |
|---|--|
| <b>Rated Current (A)</b>                | 20 A   |
| <b>Rated Voltage (V)</b>                | 480 VAC/130 VDC                              |
| <b>Horsepower Rating</b>                | 3 hp   |
| <b>Contact Configuration</b>            | 10P+G  |
| <b>Ratings Information</b>              | CURRENT INTERRUPTING                         |
| <b>Environmental Rating</b>             | IP 54/55                                     |
| <b>Short Circuit Rating</b>             | 10 kA - WITHSTAND                            |
| <b>Impact Rating</b>                    | IK09   |
| <b>Material</b>                         | METAL  |
| <b>Metal Type</b>                       | ZAMAK  |
| <b>Product Color</b>                    | METAL  |
| <b>Minimum Operating Temperature</b>    | -40F<br>-40C                                 |
| <b>Maximum Operating Temperature</b>    | 140F<br>60C                                  |
| <b>Wiring Capacity - Phase Contacts</b> | 16 AWG – 10 AWG<br>SCREW TERMINAL            |
| <b>Applicable Standards</b>             | cCSAus<br>C22.2 No. 94.2-15                  |
| <b>Accessory Size</b>                   | 5  |
| <b>Base Drawing Number</b>              | <a href="#">17-68xxx.pdf</a>                 |
| <b>Catalog</b>                          | <a href="#">meltric-catalog-dn20c-en.pdf</a> |