



DXN30 RECEPTACLE

22-34167-843-R

SPECIFICATIONS

30 A

208 VAC

IP66/IP67

5 hp

Rated Current (A)	30 A
Rated Voltage (V)	208 VAC
Horsepower Rating	5 hp
Contact Configuration	3P+N+G
Auxiliary Contacts	NO AUX
Ratings Information	CURRENT INTERRUPTING
Environmental Rating	IP 66/67
Short Circuit Rating	25 kA - CLOSE & WITHSTAND
Impact Rating	IK09
Material	POLY
Product Color	BLACK
Minimum Operating Temperature	-40F -40C
Maximum Operating Temperature	140F 60C
Wiring Capacity - Phase Contacts	14 AWG – 6 AWG SCREW TERMINAL
Hazardous Ratings	-40C < Ta < +60C Class I Zone1 AEx de IIC T5 Gb -40C < Ta < +60C Zone 21 AEx tD T77C Db Class I Div 2 Gr A,B,C,D Class II Div 2 Gr E,F,G
Applicable Standards	cCSAus C22.2 No. 182.1-13
Option(1)	PADLOCK PAWL
Option(2)	NORMALLY CLOSED LID
Accessory Size	2
Base Drawing Number	22-34xxx.pdf
Catalog	meltric-catalog-dxn30-en.pdf