



# DX9 CONNECTOR

26-93043-63M

## SPECIFICATIONS

100 A  
 480 VAC  
 IP65

<b>Rated Current (A)</b>	100 A
<b>Rated Voltage (V)</b>	480 VAC
<b>Contact Configuration</b>	3P+G
<b>Ratings Information</b>	CURRENT INTERRUPTING
<b>Environmental Rating</b>	IP 65
<b>Short Circuit Rating</b>	10 kA - CLOSE & WITHSTAND
<b>Impact Rating</b>	IK10
<b>Material</b>	METAL
<b>Metal Type</b>	ALUMINUM PAINTED
<b>Product Color</b>	BLACK
<b>Thread Size</b>	M63
<b>Cable Range</b>	1.420-1.890"
<b>Minimum Operating Temperature</b>	-40F -40C
<b>Maximum Operating Temperature</b>	140F 60C
<b>Wiring Capacity - Phase Contacts</b>	1/0 AWG – 2/0 AWG SCREW TERMINAL
<b>Hazardous Ratings</b>	Zone 1 & 2 Gb T5-T6 Zone 21 & 22 tD T80C-T90C
<b>Accessory Size</b>	9
<b>Base Drawing Number</b>	<a href="#">26-93xxx-xxx.pdf</a>
<b>Catalog</b>	<a href="#">meltric-catalog-dx9-en.pdf</a>