



# DR150 INLET

31-98233-K16

## SPECIFICATIONS

150 A  
 208 VAC  
 Type 4X

|   |  |
|---|--|
| <b>Rated Current (A)</b>                | 150 A  |
| <b>Rated Voltage (V)</b>                | 208 VAC                                      |
| <b>Contact Configuration</b>            | 3P+G   |
| <b>Auxiliary Contacts</b>               | NO AUX                                       |
| <b>Ratings Information</b>              | CURRENT INTERRUPTING                         |
| <b>Environmental Rating</b>             | Type 4X<br>IP 66/67                          |
| <b>Short Circuit Rating</b>             | 100 kA - CLOSE & WITHSTAND                   |
| <b>Impact Rating</b>                    | IK09   |
| <b>Material</b>                         | POLY   |
| <b>Product Color</b>                    | BLUE   |
| <b>Minimum Operating Temperature</b>    | -40F<br>-40C                                 |
| <b>Maximum Operating Temperature</b>    | 140F<br>60C                                  |
| <b>Wiring Capacity - Phase Contacts</b> | 4 AWG - 2/0 AWG<br>SCREW TERMINAL            |
| <b>Applicable Standards</b>             | UL 1682<br>cCSAus<br>C22.2 No. 182.1-13      |
| <b>Accessory Size</b>                   | 5  |
| <b>Base Drawing Number</b>              | <a href="#">31-98xxx-kxx.PDF</a>             |
| <b>Catalog</b>                          | <a href="#">meltric-catalog-dr150-en.pdf</a> |