



DS100C HAZ RECEPTACLE

36-64176-C-K07-HAZ

SPECIFICATIONS

100 A
 125/250 VAC
 Type 4X
 5 hp/10 hp

| | |
|---|---|
| Rated Current (A) | 100 A |
| Rated Voltage (V) | 125/250 VAC |
| Horsepower Rating | 5 hp/10 hp |
| Contact Configuration | 2P+N+G |
| Auxiliary Contacts | NO AUX |
| Ratings Information | NON-CURRENT INTERRUPTING |
| Environmental Rating | Type 4X |
| Short Circuit Rating | 100 kA - CLOSE & WITHSTAND |
| Impact Rating | IK09 |
| Material | METAL |
| Metal Type | ZAMAK |
| Product Color | BLACK |
| Minimum Operating Temperature | -40F -40C |
| Maximum Operating Temperature | 104F 40C |
| Wiring Capacity - Phase Contacts | 10 AWG – 2 AWG SCREW TERMINAL |
| Hazardous Ratings | Class I Zone IIC Class I Div 2 Groups A,B,C,D T6 |
| Applicable Standards | cCSAus C22.2 No. 182.1-07 |
| Accessory Size | 4 |
| Base Drawing Number | 36-64xxx-C-Kxx-xxx-haz.pdf |
| Catalog | meltric-catalog-zone2-ds100c-en.pdf |