



DR250 RECEPTACLE

39-24237-K16-972-375-NC

SPECIFICATIONS

250 A

120/208 VAC

Type 4X

| | |
|---|--|
| Rated Current (A) | 250 A |
| Rated Voltage (V) | 120/208 VAC |
| Contact Configuration | 3P+N+G |
| Auxiliary Contacts | +2 AUX |
| Ratings Information | NON-CURRENT INTERRUPTING |
| Environmental Rating | Type 4X IP 66/67 |
| Short Circuit Rating | 10 kA - CLOSE & WITHSTAND |
| Impact Rating | IK10 |
| Material | METAL |
| Metal Type | ALUMINUM |
| Product Color | BLUE |
| Minimum Operating Temperature | -40F -40C |
| Maximum Operating Temperature | 140F 60C |
| Wiring Capacity - Phase Contacts | 4 AWG - 4/0 AWG SCREW TERMINAL |
| Applicable Standards | UL 1682 cCSAus C22.2 No. 182.1-13 |
| Option(1) | MUSHROOM PAWL |
| Option(2) | NORMALLY CLOSED LID |
| Accessory Size | 6 |
| Base Drawing Number | 39-24xxx-kxx.PDF |
| Catalog | meltric-catalog-dr250-en.pdf |