



# DSN30 RECEPTACLE

63-34163-972-375-843

## SPECIFICATIONS

30 A

208 VAC

Type 4X & IP69

5 hp

|                                  |                                                                                     |
|----------------------------------|-------------------------------------------------------------------------------------|
| Rated Current (A)                | 30 A                                                                                |
| Rated Voltage (V)                | 208 VAC                                                                             |
| Horsepower Rating                | 5 hp                                                                                |
| Contact Configuration            | 3P+G                                                                                |
| Auxiliary Contacts               | +2 AUX                                                                              |
| Ratings Information              | SWITCH RATED<br>BRANCH CIRCUIT DISCONNECT SWITCH<br>MOTOR CIRCUIT DISCONNECT SWITCH |
| Environmental Rating             | Type 4X<br>IP 66/67<br>IP 69                                                        |
| Short Circuit Rating             | 100 kA - CLOSE & WITHSTAND                                                          |
| Impact Rating                    | IK09                                                                                |
| Material                         | POLY                                                                                |
| Product Color                    | BLUE                                                                                |
| Minimum Operating Temperature    | -40F<br>-40C                                                                        |
| Maximum Operating Temperature    | 140F<br>60C                                                                         |
| Wiring Capacity - Phase Contacts | 14 AWG – 8 AWG<br>SCREW TERMINAL                                                    |
| Applicable Standards             | UL 1682<br>UL 2682<br>cCSAus<br>C22.2 No. 182.1-13                                  |
| Option(1)                        | PADLOCKABLE MUSHROOM PAWL                                                           |
| Accessory Size                   | 2                                                                                   |
| Base Drawing Number              | <a href="#">63-34xxx.PDF</a>                                                        |
| Catalog                          | <a href="#">meltric-catalog-dsn30-en.pdf</a>                                        |