



# DSDC1 INLET

33-18109-4X

## SPECIFICATIONS

20 A

130 VDC

Type 4X

|                                  |                                             |
|----------------------------------|---------------------------------------------|
| Rated Current (A)                | 20 A                                        |
| Rated Voltage (V)                | 130 VDC                                     |
| Contact Configuration            | 2P+G                                        |
| Ratings Information              | NON-CURRENT INTERRUPTING                    |
| Environmental Rating             | Type 4X<br>IP 66/67                         |
| Impact Rating                    | IK09                                        |
| Material                         | POLY                                        |
| Product Color                    | BLUE                                        |
| Minimum Operating Temperature    | -40F<br>-40C                                |
| Maximum Operating Temperature    | 140F<br>60C                                 |
| Wiring Capacity - Phase Contacts | 14 AWG – 8 AWG<br>SCREW TERMINAL            |
| Applicable Standards             | UL 1682<br>cCSAus<br>C22.2 No. 182.1-13     |
| Option(1)                        | TYPE 4X WATERTIGHTNESS                      |
| Accessory Size                   | 2                                           |
| Base Drawing Number              | <a href="#">33-18xxx-xxx.pdf</a>            |
| Catalog                          | <a href="#">meltric-catalog-dsdc-en.pdf</a> |