



# DN20c INLET

17-68181-A188

## SPECIFICATIONS

15 A

480 VAC/130 VDC

IP54/IP55

3 hp

|                                  |                                              |
|----------------------------------|----------------------------------------------|
| Rated Current (A)                | 15 A                                         |
| Rated Voltage (V)                | 480 VAC/130 VDC                              |
| Horsepower Rating                | 3 hp                                         |
| Contact Configuration            | 18P+G                                        |
| Ratings Information              | CURRENT INTERRUPTING                         |
| Environmental Rating             | IP 54/55                                     |
| Short Circuit Rating             | 10 kA - WITHSTAND                            |
| Impact Rating                    | IK09                                         |
| Material                         | METAL                                        |
| Metal Type                       | ZAMAK                                        |
| Product Color                    | METAL                                        |
| Minimum Operating Temperature    | -40F<br>-40C                                 |
| Maximum Operating Temperature    | 140F<br>60C                                  |
| Wiring Capacity - Phase Contacts | 16 AWG – 10 AWG<br>SCREW TERMINAL            |
| Applicable Standards             | cCSAus<br>C22.2 No. 94.2-15                  |
| Option(1)                        | STRAIGHT INSERTION                           |
| Accessory Size                   | 5                                            |
| Base Drawing Number              | <a href="#">17-68xxx.pdf</a>                 |
| Catalog                          | <a href="#">meltric-catalog-dn20c-en.pdf</a> |