



# DR7c RECEPTACLE

39-34951

## SPECIFICATIONS

50 A

600 VAC/130 VDC

IP66/IP67/IP69

|                                         |                                                  |
|-----------------------------------------|--------------------------------------------------|
| <b>Rated Current (A)</b>                | 50 A                                             |
| <b>Rated Voltage (V)</b>                | 600 VAC/130 VDC                                  |
| <b>Contact Configuration</b>            | 5P+G                                             |
| <b>Auxiliary Contacts</b>               | NO AUX                                           |
| <b>Ratings Information</b>              | NON-CURRENT INTERRUPTING                         |
| <b>Environmental Rating</b>             | IP 66/67/69                                      |
| <b>Impact Rating</b>                    | IK09                                             |
| <b>Material</b>                         | METAL                                            |
| <b>Metal Type</b>                       | ALUMINUM                                         |
| <b>Product Color</b>                    | GRAY                                             |
| <b>Minimum Operating Temperature</b>    | -40F<br>-40C                                     |
| <b>Maximum Operating Temperature</b>    | 140F<br>60C                                      |
| <b>Wiring Capacity - Phase Contacts</b> | 14 AWG – 8 AWG<br>SCREW TERMINAL                 |
| <b>Accessory Size</b>                   | 4                                                |
| <b>Base Drawing Number</b>              | <a href="#">39-349xx.pdf</a>                     |
| <b>Catalog</b>                          | <a href="#">meltric-catalog-ds7c-dr7c-en.pdf</a> |