



# PN7c RECEPTACLE

03-P4041-824-300-NC

## SPECIFICATIONS

15 A

480 VAC

IP66/IP67

|   |   |
|---|---|
| <b>Rated Current (A)</b>                | 15 A  |
| <b>Rated Voltage (V)</b>                | 480 VAC                                     |
| <b>Contact Configuration</b>            | 4P+G  |
| <b>Ratings Information</b>              | CURRENT INTERRUPTING                        |
| <b>Environmental Rating</b>             | IP 66/67                                    |
| <b>Impact Rating</b>                    | IK08  |
| <b>Material</b>                         | POLY  |
| <b>Product Color</b>                    | BLUE  |
| <b>Minimum Operating Temperature</b>    | -40F<br>-40C                                |
| <b>Maximum Operating Temperature</b>    | 140F<br>60C                                 |
| <b>Wiring Capacity - Phase Contacts</b> | 18 AWG – 10 AWG<br>SCREW TERMINAL           |
| <b>Applicable Standards</b>             | UL 1682<br>cCSAus<br>C22.2 No. 94.2-15      |
| <b>Option(1)</b>                        | SCREW TYPE LOCKING PAWL                     |
| <b>Option(2)</b>                        | SELF-RETURNING LID                          |
| <b>Accessory Size</b>                   | 1   |
| <b>Base Drawing Number</b>              | <a href="#">03-p40x1.pdf</a>                |
| <b>Catalog</b>                          | <a href="#">meltric-catalog-pn7c-en.pdf</a> |