



# PN20 INLET

09-N4075-001-824-300

## SPECIFICATIONS

20 A

125 VAC

Type 4X

<b>Rated Current (A)</b>	20 A
<b>Rated Voltage (V)</b>	125 VAC
<b>Contact Configuration</b>	1P+N+G
<b>Ratings Information</b>	CURRENT INTERRUPTING
<b>Environmental Rating</b>	Type 4X IP 66/67
<b>Impact Rating</b>	IK09
<b>Material</b>	METAL
<b>Metal Type</b>	ZAMAK
<b>Product Color</b>	BLUE
<b>Minimum Operating Temperature</b>	-40F -40C
<b>Maximum Operating Temperature</b>	140F 60C
<b>Wiring Capacity - Phase Contacts</b>	14 AWG – 8 AWG SCREW TERMINAL
<b>Applicable Standards</b>	UL 1682 cCSAus C22.2 No. 182.1-07
<b>Option(1)</b>	REVERSE INTERIORS
<b>Option(2)</b>	SCREW TYPE LOCKING PAWL
<b>Accessory Size</b>	1
<b>Base Drawing Number</b>	<a href="#">09-N4xxx-001.PDF</a>
<b>Catalog</b>	<a href="#">meltric-catalog-pn-en.pdf</a>