



# DXN20 RECEPTACLE

22-14127-K16-843

## SPECIFICATIONS

20 A

208 VAC

IP66/IP67

3 hp

|                                         |                                                                                                                                                         |
|-----------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Rated Current (A)</b>                | 20 A                                                                                                                                                    |
| <b>Rated Voltage (V)</b>                | 208 VAC                                                                                                                                                 |
| <b>Horsepower Rating</b>                | 3 hp                                                                                                                                                    |
| <b>Contact Configuration</b>            | 3P+N+G                                                                                                                                                  |
| <b>Ratings Information</b>              | CURRENT INTERRUPTING                                                                                                                                    |
| <b>Environmental Rating</b>             | IP 66/67                                                                                                                                                |
| <b>Short Circuit Rating</b>             | 25 kA - CLOSE & WITHSTAND                                                                                                                               |
| <b>Impact Rating</b>                    | IK09                                                                                                                                                    |
| <b>Material</b>                         | POLY                                                                                                                                                    |
| <b>Product Color</b>                    | BLACK                                                                                                                                                   |
| <b>Minimum Operating Temperature</b>    | -40F<br>-40C                                                                                                                                            |
| <b>Maximum Operating Temperature</b>    | 140F<br>60C                                                                                                                                             |
| <b>Wiring Capacity - Phase Contacts</b> | 16 AWG – 10 AWG<br>SCREW TERMINAL                                                                                                                       |
| <b>Hazardous Ratings</b>                | -40C < Ta < +60C<br>Class I Zone1 AEx de IIC T5 Gb<br>-40C < Ta < +60C<br>Zone 21 AEx tD T90C Db<br>Class I Div 2 Gr A,B,C,D<br>Class II Div 2 Gr E,F,G |
| <b>Applicable Standards</b>             | cCSAus<br>C22.2 No. 182.1-13                                                                                                                            |
| <b>Option(1)</b>                        | PADLOCK PAWL                                                                                                                                            |
| <b>Accessory Size</b>                   | 1                                                                                                                                                       |
| <b>Base Drawing Number</b>              | <a href="#">22-14xxx.PDF</a>                                                                                                                            |
| <b>Catalog</b>                          | <a href="#">meltric-catalog-dxn20-en.pdf</a>                                                                                                            |