



# DXN30 INLET

22-38163-A155

## SPECIFICATIONS

30 A

208 VAC

IP66/IP67

5 hp

<b>Rated Current (A)</b>	30 A
<b>Rated Voltage (V)</b>	208 VAC
<b>Horsepower Rating</b>	5 hp
<b>Contact Configuration</b>	3P+G
<b>Auxiliary Contacts</b>	NO AUX
<b>Ratings Information</b>	CURRENT INTERRUPTING
<b>Environmental Rating</b>	IP 66/67
<b>Short Circuit Rating</b>	25 kA - CLOSE & WITHSTAND
<b>Impact Rating</b>	IK09
<b>Material</b>	POLY
<b>Product Color</b>	BLACK
<b>Minimum Operating Temperature</b>	-40F -40C
<b>Maximum Operating Temperature</b>	140F 60C
<b>Wiring Capacity - Phase Contacts</b>	14 AWG – 6 AWG SCREW TERMINAL
<b>Hazardous Ratings</b>	-40C < Ta < +60C Class I Zone1 AEx de IIC T5 Gb -40C < Ta < +60C Zone 21 AEx tD T77C Db Class I Div 2 Gr A,B,C,D Class II Div 2 Gr E,F,G
<b>Applicable Standards</b>	cCSAus C22.2 No. 182.1-13
<b>Option(1)</b>	WITH NO LOCKOUT HOLE
<b>Accessory Size</b>	2
<b>Base Drawing Number</b>	<a href="#">22-38xxx.pdf</a>
<b>Catalog</b>	<a href="#">meltric-catalog-dxn30-en.pdf</a>