



DXN60 RECEPTACLE

22-64143-843-924

SPECIFICATIONS

60 A

600 VAC

IP66/IP67

20 hp

Rated Current (A)	60 A
Rated Voltage (V)	600 VAC
Horsepower Rating	20 hp
Contact Configuration	3P+G
Auxiliary Contacts	NO AUX
Ratings Information	CURRENT INTERRUPTING
Environmental Rating	IP 66/67
Short Circuit Rating	25 kA - CLOSE & WITHSTAND
Impact Rating	IK09
Material	POLY
Product Color	BLACK
Minimum Operating Temperature	-40F -40C
Maximum Operating Temperature	140F 60C
Wiring Capacity - Phase Contacts	10 AWG - 4 AWG SCREW TERMINAL
Hazardous Ratings	-40C < Ta < +60C Class I Zone1 AEx de IIC T4 Gb -40C < Ta < +60C Zone 21 AEx tD T100C Db Class I Div 2 Gr A,B,C,D Class II Div 2 Gr E,F,G
Applicable Standards	cCSAus C22.2 No. 182.1-13
Option(1)	PADLOCK PAWL
Option(2)	METAL PAWL (ON POLY RECEPTACLE)
Accessory Size	3
Base Drawing Number	22-64xxx.pdf
Catalog	meltric-catalog-dxn60-en.pdf