



DXN60 RECEPTACLE

22-64163-843

SPECIFICATIONS

60 A

208 VAC

IP66/IP67

7.5 hp

| | |
|---|--|
| Rated Current (A) | 60 A |
| Rated Voltage (V) | 208 VAC |
| Horsepower Rating | 7.5 hp |
| Contact Configuration | 3P+G |
| Auxiliary Contacts | NO AUX |
| Ratings Information | CURRENT INTERRUPTING |
| Environmental Rating | IP 66/67 |
| Short Circuit Rating | 25 kA - CLOSE & WITHSTAND |
| Impact Rating | IK09 |
| Material | POLY |
| Product Color | BLACK |
| Minimum Operating Temperature | -40F -40C |
| Maximum Operating Temperature | 140F 60C |
| Wiring Capacity - Phase Contacts | 10 AWG – 4 AWG SCREW TERMINAL |
| Hazardous Ratings | -40C < Ta < +60C Class I Zone1 AEx de IIC T4 Gb -40C < Ta < +60C Zone 21 AEx tD T100C Db Class I Div 2 Gr A,B,C,D Class II Div 2 Gr E,F,G |
| Applicable Standards | cCSAus C22.2 No. 182.1-13 |
| Option(1) | PADLOCK PAWL |
| Accessory Size | 3 |
| Base Drawing Number | 22-64xxx.pdf |