



# DR30 RECEPTACLE

31-14187-K14-972

## SPECIFICATIONS

30 A

347/600 VAC

Type 3R

|   |   |
|---|---|
| <b>Rated Current (A)</b>                | 30 A                                    |
| <b>Rated Voltage (V)</b>                | 347/600 VAC                             |
| <b>Contact Configuration</b>            | 3P+N+G                                  |
| <b>Auxiliary Contacts</b>               | +2 AUX                                  |
| <b>Ratings Information</b>              | NON-CURRENT INTERRUPTING                |
| <b>Environmental Rating</b>             | Type 3R<br>IP 55                        |
| <b>Short Circuit Rating</b>             | 100 kA - CLOSE & WITHSTAND              |
| <b>Impact Rating</b>                    | IK09                                    |
| <b>Material</b>                         | POLY                                    |
| <b>Product Color</b>                    | BLUE                                    |
| <b>Minimum Operating Temperature</b>    | -40F<br>-40C                            |
| <b>Maximum Operating Temperature</b>    | 140F<br>60C                             |
| <b>Wiring Capacity - Phase Contacts</b> | 14 AWG – 8 AWG<br>SCREW TERMINAL        |
| <b>Applicable Standards</b>             | UL 1682<br>cCSAus<br>C22.2 No. 182.1-13 |
| <b>Accessory Size</b>                   | 2                                       |
| <b>Base Drawing Number</b>              | <a href="#">31-14xxx-kxx.PDF</a>        |