



# DR30 INLET

31-18173-K07-270

## SPECIFICATIONS

30 A

250 VAC

Type 3R

|   |   |
|---|---|
| <b>Rated Current (A)</b>                | 30 A  |
| <b>Rated Voltage (V)</b>                | 250 VAC                                     |
| <b>Contact Configuration</b>            | 3P+G  |
| <b>Auxiliary Contacts</b>               | NO AUX                                      |
| <b>Ratings Information</b>              | NON-CURRENT INTERRUPTING                    |
| <b>Environmental Rating</b>             | Type 3R<br>IP 54                            |
| <b>Short Circuit Rating</b>             | 100 kA - CLOSE & WITHSTAND                  |
| <b>Impact Rating</b>                    | IK09  |
| <b>Material</b>                         | POLY  |
| <b>Product Color</b>                    | BLUE  |
| <b>Minimum Operating Temperature</b>    | -40F<br>-40C                                |
| <b>Maximum Operating Temperature</b>    | 140F<br>60C                                 |
| <b>Wiring Capacity - Phase Contacts</b> | 14 AWG – 8 AWG<br>SCREW TERMINAL            |
| <b>Option(1)</b>                        | FOR AUXILIARY SWITCH                        |
| <b>Accessory Size</b>                   | 2   |
| <b>Base Drawing Number</b>              | <a href="#">31-18xxx-kxx.PDF</a>            |
| <b>Catalog</b>                          | <a href="#">meltric-catalog-dr30-en.pdf</a> |