MELTRIC
A COMPANY OF MARECHAL ELECTRIC

# DR50 RECEPTACLE

## 31-34173-K07-NC

### SPECIFICATIONS

50 A
250 VAC
Type 3R

| | |
|---|---|
| **Rated Current (A)** | 50 A |
| **Rated Voltage (V)** | 250 VAC |
| **Contact Configuration** | 3P+G |
| **Auxiliary Contacts** | NO AUX |
| **Ratings Information** | CURRENT INTERRUPTING |
| **Environmental Rating** | Type 3R<br>IP 55 |
| **Short Circuit Rating** | 100 kA - CLOSE & WITHSTAND |
| **Impact Rating** | IK09 |
| **Material** | POLY |
| **Product Color** | BLUE |
| **Minimum Operating Temperature** | -40F<br>-40C |
| **Maximum Operating Temperature** | 140F<br>60C |
| **Wiring Capacity - Phase Contacts** | 14 AWG – 4 AWG<br>SCREW TERMINAL |
| **Applicable Standards** | UL 1682<br>cCSAus<br>C22.2 No. 182.1-13 |
| **Option(1)** | SELF-RETURNING LID |
| **Accessory Size** | 3 |
| **Base Drawing Number** | 31-34xxx-kxx.PDF |
| **Catalog** | meltric-catalog-dr50-en.pdf |