



# DR7c INLET

31-38961-173

## SPECIFICATIONS

50 A

600 VAC/130 VDC

|   |                                  |
|---|----------------------------------|
| <b>Rated Current (A)</b>                | 50 A                             |
| <b>Rated Voltage (V)</b>                | 600 VAC/130 VDC                  |
| <b>Contact Configuration</b>            | 6P+G                             |
| <b>Auxiliary Contacts</b>               | +3 AUX                           |
| <b>Ratings Information</b>              | NON-CURRENT INTERRUPTING         |
| <b>Environmental Rating</b>             | Type 4X<br>IP 66/67<br>IP 69     |
| <b>Impact Rating</b>                    | IK09                             |
| <b>Material</b>                         | POLY                             |
| <b>Product Color</b>                    | BLUE                             |
| <b>Minimum Operating Temperature</b>    | -40F<br>-40C                     |
| <b>Maximum Operating Temperature</b>    | 140F<br>60C                      |
| <b>Wiring Capacity - Phase Contacts</b> | 14 AWG – 8 AWG<br>SCREW TERMINAL |
| <b>Applicable Standards</b>             | UL 1682                          |
| <b>Accessory Size</b>                   | 4                                |
| <b>Base Drawing Number</b>              | <a href="#">31-389xx.pdf</a>     |