



# DR150 RECEPTACLE

31-94217-K04-843

## SPECIFICATIONS

150 A

277/480 VAC

Type 4X

|                                  |                                              |
|----------------------------------|----------------------------------------------|
| Rated Current (A)                | 150 A                                        |
| Rated Voltage (V)                | 277/480 VAC                                  |
| Contact Configuration            | 3P+N+G                                       |
| Auxiliary Contacts               | NO AUX                                       |
| Ratings Information              | NON-CURRENT INTERRUPTING                     |
| Environmental Rating             | Type 4X<br>IP 66/67                          |
| Short Circuit Rating             | 100 kA - CLOSE & WITHSTAND                   |
| Impact Rating                    | IK09                                         |
| Material                         | POLY                                         |
| Product Color                    | BLUE                                         |
| Minimum Operating Temperature    | -40F<br>-40C                                 |
| Maximum Operating Temperature    | 140F<br>60C                                  |
| Wiring Capacity - Phase Contacts | 4 AWG - 2/0 AWG<br>SCREW TERMINAL            |
| Applicable Standards             | UL 1682<br>cCSAus<br>C22.2 No. 182.1-13      |
| Option(1)                        | PADLOCK PAWL                                 |
| Option(2)                        | SPARE POSITION                               |
| Accessory Size                   | 5                                            |
| Base Drawing Number              | <a href="#">31-94xxx-kxx.PDF</a>             |
| Catalog                          | <a href="#">meltric-catalog-dr150-en.pdf</a> |