



DS20 INLET

33-18167-972-4X-A155

SPECIFICATIONS

20 A

120/208 VAC

Type 4X

0.75 hp/3 hp

Rated Current (A)	20 A
Rated Voltage (V)	120/208 VAC
Horsepower Rating	0.75 hp/3 hp
Contact Configuration	3P+N+G
Auxiliary Contacts	+2 AUX
Ratings Information	SWITCH RATED BRANCH CIRCUIT DISCONNECT SWITCH MOTOR CIRCUIT DISCONNECT SWITCH
Environmental Rating	Type 4X IP 66/67
Short Circuit Rating	100 kA - CLOSE & WITHSTAND
Impact Rating	IK09
Material	POLY
Product Color	BLUE
Minimum Operating Temperature	-40F -40C
Maximum Operating Temperature	140F 60C
Wiring Capacity - Phase Contacts	14 AWG – 8 AWG SCREW TERMINAL
Applicable Standards	UL 2682 UL 1682 cCSAus C22.2 No. 182.1-13
Option(1)	TYPE 4X WATERTIGHTNESS
Option(2)	WITH NO LOCKOUT HOLE
Accessory Size	2
Base Drawing Number	33-18xxx.PDF
Catalog	meltric-catalog-ds20-en.pdf