



DS30 RECEPTACLE

33-34047-973-843-4X

SPECIFICATIONS

30 A
 277/480 VAC
 Type 4X
 3 hp/15 hp

Rated Current (A)	30 A
Rated Voltage (V)	277/480 VAC
Horsepower Rating	3 hp/15 hp
Contact Configuration	3P+N+G
Auxiliary Contacts	+3 AUX
Ratings Information	SWITCH RATED BRANCH CIRCUIT DISCONNECT SWITCH MOTOR CIRCUIT DISCONNECT SWITCH
Environmental Rating	Type 4X IP 66/67
Short Circuit Rating	100 kA - CLOSE & WITHSTAND
Impact Rating	IK09
Material	POLY
Product Color	BLUE
Minimum Operating Temperature	-40F -40C
Maximum Operating Temperature	140F 60C
Wiring Capacity - Phase Contacts	14 AWG – 4 AWG SCREW TERMINAL
Applicable Standards	UL 2682 UL 1682 cCSAus C22.2 No. 182.1-13
Option(1)	PADLOCK PAWL
Option(2)	TYPE 4X WATERTIGHTNESS
Accessory Size	3
Base Drawing Number	33-34xxx.PDF
Catalog	meltric-catalog-ds30-en.pdf